

**PRODUCT :** 6AP2  
**DESCRIPTION:** Polyester Accelerator (Cobalt)

**CHEMICAL - PHYSICAL CHARACTERISTICS**

<b>SPECIFIC GRAVITY:</b>	0.91 ± 0.100 (Kg/l at 20°C)
<b>DENSITY (WPG):</b>	7.59 ± 0.100 (lbs/gal US at 68° F)
<b>WEIGHT SOLIDS:</b>	11% ± 1
<b>VOLUME SOLIDS:</b>	8.30% ± 1
<b>VOC (material):</b>	6.76 lbs/gal US or 809.90 g/l
<b>VOC (coating):</b>	6.76 lbs/gal US or 809.90 g/l
<b>VOC Ratio:</b>	8.09 lbs VOC/lbs Solids
<b>HAPS Ratio:</b>	4.436 lbs HAPS/lbs solids

**This product meets U.S.A. TSCA regulations.**

**GENERAL PROPERTIES**

Accelerating agent for polyester. Mixing Ratio: 2%.

Before use, consult the safety data sheet for health and environmental concerns.

Keep away from ignition sources.

Keep the product in a ventilated area; do not exceed 25-28°C. Do not use the product with temperatures below 15°C and when relative humidity is high since it could affect drying times and stackability.

For further information, please refer to our technical representatives.

**SHELF LIFE:** 1 year  
Data refers to product stored in original, sealed packing.

**STORAGE:** Keep in a cool, well ventilated place; temperature should not exceed 77°- 82.4° F.

**Company Information:** SIRCA S.p.A. has a quality system certified by DNV GL ISO 9001



The information supplied are correct to the best of our knowledge. However, as the coating process depends on many variables and the present application takes place without our supervision, we cannot assume any responsibility for the final result. Sirca guarantees that chemical and physical characteristics of the products are within the reported range. Due to the large variety of substrates and application devices, the purchaser/user should test our products in his own application conditions and safety and environment circumstances. Sirca's technical and sales departments are at customer's disposal for any further information regarding correct application of our products.