



Safety Data Sheet Dye concentrates hiding white





Safety Data Sheet dated 11/3/2017, version 3

1. IDENTIFICATION

Product identifier
Mixture identification:
Trade name: Dye concentrates hiding white
Other means of identification:
Trade code: 6CPI561
Recommended use of the chemical and restrictions on use
Recommended use: Surface coating
Restrictions on use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party
Company:
Sirca S.p.A.
Address:
Viale Roma, 85
35010 S. Dono di Massanzago (PD) - ITALY
Tel. +39 0499322311
Distributed by:
GEMINI INDUSTRIES, INC.
2300 Holloway Drive
El Reno, OK 73036
USA
Tel. 1-800-262-5710
Fax 1-405-262-9310
www.gemini-coatings.com
Competent person responsible for the safety data sheet:
safety@sirca.it
Emergency phone number
For Hazardous Materials [or Dangerous Goods] Incident
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night
1-800-424-9300 / +1 703-527-3887.

2. HAZARD(S) IDENTIFICATION

Classification of the chemical
 Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
 Warning, Carc. 2, Suspected of causing cancer.
 Danger, Repr. 1B, May damage fertility or the unborn child.
 Warning, STOT SE 3, May cause drowsiness or dizziness.

Label elements
Hazard pictograms:



Danger

Hazard statements:
H225 Highly flammable liquid and vapour.
H351 Suspected of causing cancer.
H360 May damage fertility or the unborn child.
H336 May cause drowsiness or dizziness.
Precautionary statements:
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

Safety Data Sheet

Dye concentrates hiding white

P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P312 Call a POISON CENTER/doctor/... if you feel unwell.
 P370+P378 In case of fire: Use a CO₂, Foam, Chemical powders for extinction.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information

NFPA rating:



HMIS rating:

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL HAZARD		1
PERSONAL PROTECTION		

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 25% - < 48% Titanium dioxide

REACH No.: 01-2119489379-17-xxxx, CAS: 13463-67-7, EC: 236-675-5



A.6/2 Carc. 2 H351

>= 25% - < 48% 1-methoxy-2-propanol

REACH No.: 01-2119457435-35-xxxx, Index number: 603-064-00-3, CAS: 107-98-2, EC: 203-539-1



B.6/3 Flam. Liq. 3 H226



A.8/3 STOT SE 3 H336

>= 7% - < 9.9% butanone

REACH No.: 01-2119457290-43-xxxx, Index number: 606-002-00-3, CAS: 78-93-3, EC: 201-159-0



B.6/2 Flam. Liq. 2 H225



A.3/2A Eye Irrit. 2A H319



A.8/3 STOT SE 3 H336

Safety Data Sheet

Dye concentrates hiding white






>= 0.1% - < 0.2% xylene [isomer mixture]

REACH No.: 01-2119488216-32-xxxx, Index number: 601-022-00-9, CAS: 1330-20-7, EC: 215-535-7

-  B.6/3 Flam. Liq. 3 H226
-  A.10/1 Asp. Tox. 1 H304
-  A.3/2A Eye Irrit. 2A H319
-  A.8/3 STOT SE 3 H335
-  A.9/2 STOT RE 2 H373
-  A.2/2 Skin Irrit. 2 H315
-  A.1/4/Dermal Acute Tox. 4 H312
-  A.1/4/Inhal Acute Tox. 4 H332







>= 0.1% - < 0.2% 2-methoxypropanol

Index number: 603-106-00-0, CAS: 1589-47-5, EC: 216-455-5

-  B.6/3 Flam. Liq. 3 H226
-  A.7/1B Repr. 1B H360
-  A.8/3 STOT SE 3 H335
-  A.2/2 Skin Irrit. 2 H315
-  A.3/1 Eye Dam. 1 H318

>= 0.06% - < 0.1% ethylbenzene

REACH No.: 01-2119489370-35-xxxx, Index number: 601-023-00-4, CAS: 100-41-4, EC: 202-849-4

-  A.10/1 Asp. Tox. 1 H304
-  A.2/2 Skin Irrit. 2 H315
-  A.6/2 Carc. 2 H351
-  A.9/2 STOT RE 2 H373
-  B.6/2 Flam. Liq. 2 H225
-  A.1/4/Inhal Acute Tox. 4 H332

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

- Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire: Use a CO₂, Foam, Chemical powders for extinction.

Unsuitable extinguishing media:



Safety Data Sheet

Dye concentrates hiding white

None in particular.
Specific hazards arising from the chemical
Do not inhale explosion and combustion gases.
Burning produces heavy smoke.
Hazardous combustion products:
None
Explosive properties: N.A.
Oxidizing properties: N.A.
Special protective equipment and precautions for fire-fighters
Use suitable breathing apparatus.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures
Wear personal protection equipment.
Remove all sources of ignition.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.
Provide adequate ventilation.
Remove persons to safety.
Use appropriate respiratory protection.
See protective measures under point 7 and 8.
Methods and materials for containment and cleaning up
Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Exercise the greatest care when handling or opening the container.
Do not use on extensive surface areas in premises where there are occupants.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
Conditions for safe storage, including any incompatibilities
Always keep in a well ventilated place.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from flame and sparks. Avoid accumulating electrostatic charge.
Place recipients on the ground whilst decanting, and wear anti-static clothing and shoes.

Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.
Safety electric system.
Storage temperature:
Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters
1-methoxy-2-propanol - CAS: 107-98-2
(OEL (IT)) - TWA: 375 mg/m³, 100 ppm - STEL: 558 mg/m³, 150 ppm - Notes: pelle
NIOSH - TWA: 360 mg/m³, 100 ppm - STEL: 540 mg/m³, 150 ppm - Notes: 15 minutes average value
EU - TWA(8h): 375 mg/m³, 100 ppm - STEL: 563 mg/m³, 150 ppm - Notes: Skin
ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: A4 - Eye and URT irr
butanone - CAS: 78-93-3
(OEL (IT)) - TWA(8h): 600 mg/m³, 200 ppm - STEL: 900 mg/m³, 300 ppm - Behaviour: Binding
EU - TWA(8h): 600 mg/m³, 200 ppm - STEL: 900 mg/m³, 300 ppm
ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm - Notes: BEI - URT irr, CNS and PNS impair
xylene [isomer mixture] - CAS: 1330-20-7
(OEL (IT)) - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Behaviour: Binding - Notes: pelle
EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin
ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair
ethylbenzene - CAS: 100-41-4
(OEL (IT)) - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Behaviour: Binding - Notes: pelle
EU - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Notes: Skin
ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair
DNEL Exposure Limit Values

Safety Data Sheet

Dye concentrates hiding white

Titanium dioxide - CAS: 13463-67-7
 Worker Industry: 10 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
 Worker Professional: 10 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
 Consumer: 700 mg/kg/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

1-methoxy-2-propanol - CAS: 107-98-2
 Worker Industry: 553.5 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
 Worker Industry: 50.6 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 369 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 18.1 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 43.9 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 3.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

butanone - CAS: 78-93-3
 Worker Industry: 1161 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 600 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 412 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 106 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 31 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

xylene [isomer mixture] - CAS: 1330-20-7
 Worker Industry: 180 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 77 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 108 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 1872 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
 Consumer: 12.5 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

ethylbenzene - CAS: 100-41-4
 Worker Industry: 180 mg/kg/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 293 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
 Worker Industry: 77 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

Titanium dioxide - CAS: 13463-67-7
 Target: Fresh Water - Value: 0.127 mg/l
 Target: Marine water - Value: 0.127 mg/l
 Target: Soil (agricultural) - Value: 100 mg/kg
 Target: Marine water sediments - Value: 100 mg/kg - Notes:: dry
 Target: Freshwater sediments - Value: 1000 mg/kg - Notes:: dry
 Target: Soil (agricultural) - Value: 100 mg/kg - Notes:: alimento
 Target: orally (secondary poisoning) - Value: 1667 mg/kg

1-methoxy-2-propanol - CAS: 107-98-2
 Target: Fresh Water - Value: 10 mg/l
 Target: Marine water - Value: 1 mg/l
 Target: occasional emission - Value: 100 mg/l
 Target: STP - Value: 100 mg/l
 Target: Freshwater sediments - Value: 41.6 mg/kg
 Target: Marine water sediments - Value: 4.17 mg/kg
 Target: Soil (agricultural) - Value: 2.47 mg/kg

butanone - CAS: 78-93-3
 Target: Marine water - Value: 55.8 mg/l
 Target: Fresh Water - Value: 55.8 mg/l
 Target: occasional emission - Value: 55.8 mg/l
 Target: STP - Value: 709 mg/l
 Target: Freshwater sediments - Value: 284.7 mg/kg dwt
 Target: Marine water sediments - Value: 284.7 mg/kg dwt
 Target: Soil (agricultural) - Value: 22.5 mg/kg
 Target: orally (secondary poisoning) - Value: 1000 mg/kg

xylene [isomer mixture] - CAS: 1330-20-7
 Target: Fresh Water - Value: 0.327 mg/l
 Target: Fresh Water - Value: 0.327 mg/l
 Target: occasional emission - Value: 0.327 mg/l
 Target: Microorganisms in sewage treatments - Value: 6.58 mg/l
 Target: Soil (agricultural) - Value: 2.31 mg/kg - Notes:: dry
 Target: Marine water sediments - Value: 12.46 mg/kg - Notes:: dry
 Target: Freshwater sediments - Value: 12.46 mg/kg - Notes:: dry

ethylbenzene - CAS: 100-41-4
 Target: Fresh Water - Value: 0.1 mg/l
 Target: Marine water - Value: 0.01 mg/l
 Target: Marine water sediments - Value: 13.7 mg/l
 Target: Freshwater sediments - Value: 13.7 mg/l
 Target: occasional emission - Value: 0.1 mg/l

Appropriate engineering controls:
 None

Individual protection measures

Eye protection:
 Use close fitting safety goggles, don't use eye lens.

Safety Data Sheet

Dye concentrates hiding white

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:	liquid
Odour:	characteristic
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	< 1° C
Initial boiling point and boiling range:	> 55° C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	< 21°C - < 69.8 °F
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	1.3800 Kg/l a 20°C
Solubility in water:	N.A.
Solubility in oil:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Auto-ignition temperature:	> 250° C
Decomposition temperature:	N.A.
Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

10. STABILITY AND REACTIVITY

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

No dangerous reaction is stored and used appropriately.

Conditions to avoid

Avoid accumulating electrostatic charge.

Vapours can form explosive mixtures with air.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

Titanium dioxide - CAS: 13463-67-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 6.82 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

b) skin corrosion/irritation:

Test: Eye Irritant - Species: Rabbit No

Test: Skin Irritant - Species: Rabbit No

d) respiratory or skin sensitisation:

Test: Skin Sensitization - Species: Mouse No

i) STOT-repeated exposure:

Test: NOAEL - Species: Rat 3500 mg/kg/day - Source: polmoni

1-methoxy-2-propanol - CAS: 107-98-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 4016 mg/kg

Test: LC0 - Route: Inhalation Vapour - Species: Rat > 7000 Ppm - Duration: 6h

Safety Data Sheet

Dye concentrates hiding white

- Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg
- b) skin corrosion/irritation:
Test: Skin Irritant Negative
- c) serious eye damage/irritation:
Test: Eye Irritant Negative
- butanone - CAS: 78-93-3
- a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat = 2737 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit = 6480 mg/kg
Test: LC50 - Route: Inhalation - Species: Rat = 23.5 mg/l - Duration: 8h
- b) skin corrosion/irritation:
Test: Skin Corrosive - Species: Rabbit Negative - Notes: moderatamente irritante
- xylene [isomer mixture] - CAS: 1330-20-7
- a) acute toxicity:
Test: LD50 - Route: Inhalation - Species: Rat = 27 mg/l - Duration: 4h
Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit = 12126 mg/kg
- ethylbenzene - CAS: 100-41-4
- a) acute toxicity:
Test: LD50 - Route: Skin - Species: Rabbit = 15400 mg/kg
Test: LC50 - Route: Inhalation - Species: Rat = 4000 Ppm - Duration: 4h
- d) respiratory or skin sensitisation:
Test: Skin Sensitization - Route: Skin - Species: Cavia porcellus Negative

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

Titanium dioxide - Group 2B
xylene [isomer mixture] - Group 3
ethylbenzene - Group 2B.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

Titanium dioxide - CAS: 13463-67-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96
Endpoint: EC50 - Species: Algae = 61 mg/l - Duration h: 72
Endpoint: EC50 - Species: Daphnia > 1000 mg/l - Duration h: 48

1-methoxy-2-propanol - CAS: 107-98-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 6800 mg/l - Duration h: 96
Endpoint: LC50 - Species: Daphnia > 23300 mg/l - Duration h: 48
Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 168 - Notes: - (7d)

f) Effects in sewage plants:

Endpoint: EC50 - Species: Active mud > 1000 mg/l - Duration h: 3

butanone - CAS: 78-93-3

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 3220 mg/l - Duration h: 96
Endpoint: EC50 - Species: Daphnia > 520 mg/l - Duration h: 48

xylene [isomer mixture] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 48
Endpoint: LC50 - Species: Fish = 3.2 mg/l - Duration h: 96
Endpoint: LC50 - Species: Algae = 2.6 mg/l - Duration h: 73

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 42.3 mg/l - Duration h: 96

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

None



Safety Data Sheet

Dye concentrates hiding white

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

UN number

ADR-UN Number: 1263
DOT-UN Number: 1263
IATA-UN Number: 1263
IMDG-UN Number: 1263

UN proper shipping name

ADR-Shipping Name: Paint Related material
DOT-Shipping Name: Paint Related material
IATA-Shipping Name: Paint Related material
IMDG-Shipping Name: Paint Related material

Transport hazard class(es)

ADR-Class: 3
DOT-Class: 3
IATA-Class: 3
IMDG-Class: 3

Packing group

ADR-Packing Group: II
DOT-Packing Group: II
IATA-Packing group: II
IMDG-Packing group: II

Environmental hazards

ADR-Environmental Pollutant: No
IMDG-Marine pollutant: No

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)
No

Special precautions

ADR-Tunnel Restriction Code: D/E
DOT-Special provisions: 149, B52, IB2, T4, TP1, TP8, TP28
IATA-Passenger Aircraft: 353
IATA-Cargo Aircraft: 364
IATA-S.P.: A72
IATA-ERG: 8L
IMDG-EmS: F-E, S-E
IMDG-Storage category: B
IMDG-Storage notes: None

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: all the components are listed on the TSCA inventory.

TSCA listed substances:

ethylbenzene is listed in TSCA Section 4.

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: no substances listed.

Section 313 – Toxic chemical list: xylene [isomer mixture], ethylbenzene.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: butanone - Reportable quantity: 5000 pounds

xylene [isomer mixture] - Reportable quantity: 100 pounds

ethylbenzene - Reportable quantity: 1000 pounds.

Reportable quantity for mixture: 54253.47222 pounds.

CAA - Clean Air Act

CAA listed substances:

1-methoxy-2-propanol is listed in CAA Section 112(b) - HON

butanone is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

xylene [isomer mixture] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

ethylbenzene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

xylene [isomer mixture] is listed in CWA Section 311, Section 304

ethylbenzene is listed in CWA Section 311, Section 304, Section 307.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:



Safety Data Sheet

Dye concentrates hiding white

ethylbenzene - Listed as carcinogen.

Massachusetts Right to know
Substance(s) listed under Massachusetts Right to know:
Titanium dioxide
1-methoxy-2-propanol
butanone
xylene [isomer mixture]
ethylbenzene.

New Jersey Right to know
Substance(s) listed under New Jersey Right to know:
Titanium dioxide
1-methoxy-2-propanol
butanone
xylene [isomer mixture]
ethylbenzene.

Pennsylvania Right to know
Substance(s) listed under Pennsylvania Right to know:
Titanium dioxide
1-methoxy-2-propanol
butanone
xylene [isomer mixture]
ethylbenzene.

16. OTHER INFORMATION

Text of phrases referred to under heading 3:

H351 Suspected of causing cancer.
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H304 May be fatal if swallowed and enters airways.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H315 Causes skin irritation.
H312 Harmful in contact with skin.
H332 Harmful if inhaled.
H360 May damage fertility or the unborn child.
H318 Causes serious eye damage.

Safety Data Sheet dated 11/3/2017, version 3

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.



Safety Data Sheet

Dye concentrates hiding white

TLV: Threshold Limiting Value.
TWA: Time-weighted average