

PRODUCT : 6CT087
DESCRIPTION: Polyurethane Hardener

CHEMICAL - PHYSICAL CHARACTERISTICS

SPECIFIC GRAVITY:	0.970 ± 0.100 (Kg/l at 20°C)
DENSITY (WPG):	8.10 ± 0.100 (lbs/gal US at 68° F)
WEIGHT SOLIDS:	20% ± 1
VOLUME SOLIDS:	12.17% ± 1
VOC (material):	6.48 lbs/gal US or 776.00 g/l
VOC (coating):	6.48 lbs/gal US or 776.00 g/l
VOC Ratio:	4.00 lbs VOC/lbs Solids
HAPS Ratio:	1.70 lbs HAPS/lbs solids

This product meets U.S.A. TSCA regulations.

GENERAL PROPERTIES

This Polyurethane Hardener is suitable for pigmented basecoats and topcoats with good elasticity, good body, good wetting and pot-life. This hardener has a low light fastness skills and low reactivity (long drying times).

For further information, please refer to our technical representatives.

Companion Products:

6FPB0015 White PU Primer
6OP006Gx0 White PU Topcoat

SHELF LIFE: 1 year
Data refers to product stored in original, sealed packing.

STORAGE: Keep in a cool, well ventilated place; temperature should not exceed 77°- 82.4° F.

Company Information: SIRCA S.p.A. has a quality system certified by DNV GL ISO 9001



The information supplied are correct to the best of our knowledge. However, as the coating process depends on many variables and the present application takes place without our supervision, we cannot assume any responsibility for the final result. Sirca guarantees that chemical and physical characteristics of the products are within the reported range. Due to the large variety of substrates and application devices, the purchaser/user should test our products in his own application conditions and safety and environment circumstances. Sirca's technical and sales departments are at customer's disposal for any further information regarding correct application of our products.