



Safety Data Sheet Dark Walnut concentrated stain






Safety Data Sheet dated 10/2/2014, version 2

1. IDENTIFICATION

Product identifier
Mixture identification:
Trade name: Dark Walnut concentrated stain
Other means of identification:
Trade code: 6CTE5961
Recommended use of the chemical and restrictions on use
Recommended use: Surface coating
Restrictions on use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party
Company:
Sirca S.p.A.
Address:
Viale Roma, 85
35010 S. Dono di Massanzago (PD) - ITALY
Tel. +39 0499322311
Competent person responsible for the safety data sheet:
safety@sirca.it
Emergency phone number
Sirca S.p.A. +39 049 9322311 (08.00 - 17.00) Rome Time - from Monday to Friday

2. HAZARD(S) IDENTIFICATION

Classification of the chemical
 Warning, Flam. Liq. 3, Flammable liquid and vapour.
 Warning, Eye Irrit. 2A, Causes serious eye irritation.
 Warning, Skin Sens. 1, May cause an allergic skin reaction.
 Danger, Repr. 1B, May damage fertility or the unborn child.
 Warning, STOT SE 3, May cause drowsiness or dizziness.

Label elements

Symbols:



Danger

Hazard statements:

H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H360 May damage fertility or the unborn child.
H336 May cause drowsiness or dizziness.

Precautionary statements:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash ... Thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 IF ON SKIN: Wash with plenty of water and soap.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Safety Data Sheet

Dark Walnut concentrated stain

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P312 Call a POISON CENTER/doctor/... if you feel unwell.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P363 Wash contaminated clothing before reuse.
 P370+P378 In case of fire: Use use CO2, Foam, Chemical powders for extinction.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information

NFPA rating:



HMIS rating:

| | | |
|---------------------|---|---|
| HEALTH | * | 2 |
| FLAMMABILITY | | 3 |
| PHYSICAL HAZARD | | 1 |
| PERSONAL PROTECTION | | |

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 48% - < 75% 1-methoxy-2-propanol

REACH No.: 01-2119457435-35-xxxx, Index number: 603-064-00-3, CAS: 107-98-2, EC: 203-539-1



B.6/3 Flam. Liq. 3 H226



A.8/3 STOT SE 3 H336

>= 9.9% - < 12.5% 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether

REACH No.: 01-2119475104-44-xxxx, Index number: 603-096-00-8, CAS: 112-34-5, EC: 203-961-6



A.3/2A Eye Irrit. 2A H319

>= 7% - < 9.9% 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve





REACH No.: 01-2119475108-36-xxxx, Index number: 603-014-00-0, CAS: 111-76-2, EC: 203-905-0





A.3/2A Eye Irrit. 2A H319

Safety Data Sheet

Dark Walnut concentrated stain

-  A.2/2 Skin Irrit. 2 H315
-  A.1/4/Oral Acute Tox. 4 H302
-  A.1/4/Dermal Acute Tox. 4 H312
-  A.1/4/Inhal Acute Tox. 4 H332

>= 5% - < 7% trisodium bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-)
REACH No.: 01-2119969289-17-xxxx, CAS: 57693-14-8, EC: 260-906-9

-  A.3/2A Eye Irrit. 2A H319
 -  A.4.2/1 Skin Sens. 1 H317
- US-HAE/C3 Aquatic Chronic 3 H412

>= 0.2% - < 0.25% 2-methoxypropanol
Index number: 603-106-00-0, CAS: 1589-47-5, EC: 216-455-5

-  B.6/3 Flam. Liq. 3 H226
-  A.7/1B Repr. 1B H360
-  A.8/3 STOT SE 3 H335
-  A.2/2 Skin Irrit. 2 H315
-  A.3/1 Eye Dam. 1 H318

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire, use CO₂, Foam, Chemical powders

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:

N.A.

Oxidizing properties:

N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .



Safety Data Sheet

Dark Walnut concentrated stain

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures
Wear personal protection equipment.
Remove all sources of ignition.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.
Provide adequate ventilation.
Remove persons to safety.
Use appropriate respiratory protection.
See protective measures under point 7 and 8.
Methods and materials for containment and cleaning up
Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Exercise the greatest care when handling or opening the container.
Do not use on extensive surface areas in premises where there are occupants.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
Conditions for safe storage, including any incompatibilities
Always keep in a well ventilated place.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from flame and sparks. Avoid accumulating electrostatic charge.
Place recipients on the ground whilst decanting, and wear anti-static clothing and shoes.

Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.
Safety electric system.
Storage temperature:
Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

1-methoxy-2-propanol - CAS: 107-98-2
AGS - LTE: 375 mg/m³, 100 ppm - STE: 558 mg/m³, 150 ppm - Notes: pelle
TLV TWA - 100 ppm - 368,59 mg/m³
TLV STEL - 150 ppm - 552,88 mg/m³
VLE 8h - 375 mg/m³ - 100 ppm
VLE short - 568 mg/m³ - 150 ppm
2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5
AGS - LTE(8h): 67.5 mg/m³, 10 ppm - STE: 101.2 mg/m³, 15 ppm - Behaviour: Binding
EU - LTE(8h): 67.5 mg/m³, 10 ppm - STE: 101.2 mg/m³, 15 ppm
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2
AGS - LTE(8h): 98 mg/m³, 20 ppm - STE: 246 mg/m³, 50 ppm - Behaviour: Binding - Notes: pelle
EU - LTE(8h): 98 mg/m³, 20 ppm - STE: 246 mg/m³, 50 ppm - Notes: Skin
ACGIH - LTE: 96.66 mg/m³, 20 ppm - Notes: A3

DNEL Exposure Limit Values

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2
Worker Industry: 89 mg/kg - Consumer: 44.5 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects
Worker Industry: 135 ppm - Consumer: 426 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
Worker Industry: 50 ppm - Consumer: 123 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
Worker Industry: 75 mg/kg - Consumer: 38 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Industry: 20 ppm - Consumer: 49 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Consumer: 13.4 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects
Consumer: 3.2 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
trisodium bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-) - CAS: 57693-14-8
Worker Industry: 24.5 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Worker Industry: 27.78 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Consumer: 14.7 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Consumer: 16.7 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Safety Data Sheet

Dark Walnut concentrated stain

Consumer: 8.33 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

Target: Fresh Water - Value: 8.8 mg/l
 Target: Marine water - Value: 0.88 mg/l
 Target: Microorganisms in sewage treatments - Value: 463 mg/l
 Target: Freshwater sediments - Value: 34.6 mg/kg
 Target: Marine water sediments - Value: 3.46 mg/kg
 Target: Soil (agricultural) - Value: 2.8 mg/l

trisodium bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-) - CAS: 57693-14-8

Target: orally (secondary poisoning) - Value: 33.3 mg/kg
 Target: Soil (agricultural) - Value: 600 mg/kg
 Target: Fresh Water - Value: 3 µg/L
 Target: Marine water - Value: 0.3 µg/L
 Target: Freshwater sediments - Value: 3000 mg/kg
 Target: Marine water sediments - Value: 300 mg/kg
 Target: STP - Value: 0.781 mg/l

Appropriate engineering controls:
 None

Individual protection measures

Eye protection:
 Use close fitting safety goggles, don't use eye lens.

Protection for skin:
 Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:
 Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:
 Use adequate protective respiratory equipment.

Thermal Hazards:
 None

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---|
| Appearance and colour: | liquid |
| Odour: | characteristic |
| Odour threshold: | N.A. |
| pH: | N.A. |
| Melting point / freezing point: | < 1° C |
| Initial boiling point and boiling range: | > 55° C |
| Solid/gas flammability: | N.A. |
| Upper/lower flammability or explosive limits: | N.A. |
| Vapour density: | N.A. |
| Flash point: | 21°C <= fp < 55°C (69.8°F <= fp < 131°F) |
| Evaporation rate: | N.A. |
| Vapour pressure: | N.A. |
| Relative density: | 0.9400 Kg/l a 20°C |
| Solubility in water: | N.A. |
| Solubility in oil: | N.A. |
| Partition coefficient (n-octanol/water): | N.A. |
| Auto-ignition temperature: | > 250° C |
| Decomposition temperature: | N.A. |
| Miscibility: | N.A. |
| Fat Solubility: | N.A. |
| Conductivity: | N.A. |
| Substance Groups relevant properties | N.A. |

10. STABILITY AND REACTIVITY

Reactivity
 It may generate dangerous reactions (See subsections below)

Chemical stability
 It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions
 No dangerous reaction is stored and used appropriately.

Conditions to avoid
 Avoid accumulating electrostatic charge.
 Vapours can form explosive mixtures with air.

Incompatible materials
 Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products
 None.

Safety Data Sheet

Dark Walnut concentrated stain

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rabbit = 3 mg/l - Duration: 2h

Test: LD50 - Route: Oral - Species: Rat = 3384 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 3764 mg/kg

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 1480 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit 435 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Rat male 2.4 mg/l - Duration: 4h

Test: LC50 - Route: Inhalation Vapour - Species: Rat Female 2.2 mg/l - Duration: 4h

b) skin corrosion/irritation:

Test: Skin Irritant - Route: Skin - Species: Rabbit Positive

Test: Eye Irritant - Species: Rabbit Positive

trisodium bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-) - CAS: 57693-14-8

a) acute toxicity:

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg body weight - Source: OECD402

1-methoxy-2-propanol - CAS: 107-98-2

LD50 (RABBIT) ORAL: 8 G/KG (8000 MG/KG)

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - Group 3.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 1490 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 1815 mg/l - Duration h: 24

c) Bacteria toxicity:

Endpoint: EC50 - Species: Active mud > 700 mg/l - Duration h: 16

trisodium bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-) - CAS: 57693-14-8

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 30.2 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 3 mg/l - Duration h: 96

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

None

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

UN number

ADR-UN Number: 1263

DOT-UN Number: 1263

IATA-UN Number: 1263

IMDG-UN Number: 1263

UN proper shipping name

ADR-Shipping Name: Paint Related material

DOT-Shipping Name: Paint Related material



Safety Data Sheet

Dark Walnut concentrated stain

| | | |
|--|-----|-----------------------------------|
| IATA-Shipping Name: | | Paint Related material |
| IMDG-Shipping Name: | | Paint Related material |
| Transport hazard class(es) | | |
| ADR-Class: | 3 | |
| DOT-Class: | 3 | |
| IATA-Class: | 3 | |
| IMDG-Class: | 3 | |
| Packing group | | |
| ADR-Packing Group: II | | |
| DOT-Packing Group: II | | |
| IATA-Packing group: II | | |
| IMDG-Packing group: II | | |
| Environmental hazards | | |
| ADR-Environmental Pollutant: No | | |
| IMDG-Marine pollutant: | No | |
| Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code) | | |
| No | | |
| Special precautions | | |
| ADR-Tunnel Restriction Code: | D/E | |
| DOT-Special provisions: | | 149, B52, IB2, T4, TP1, TP8, TP28 |
| IATA-Passenger Aircraft: | | 353 |
| IATA-Cargo Aircraft: | | 364 |
| IATA-S.P.: | | A72 |
| IATA-ERG: | | 8L |
| IMDG-EmS: | | F-E, <u>S-E</u> |
| IMDG-Storage category: | | B |
| IMDG-Storage notes: | | None |

15. REGULATORY INFORMATION

USA - Federal regulations

- TSCA - Toxic Substances Control Act
 - TSCA inventory: all the components are listed on the TSCA inventory.
 - TSCA listed substances:
 - 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve is listed in TSCA Section 4, Section 12b.
- SARA - Superfund Amendments and Reauthorization Act
 - Section 302 – Extremely Hazardous Substances: no substances listed.
 - Section 304 – Hazardous substances: no substances listed.
 - Section 313 – Toxic chemical list: no substances listed.
- CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
 - No substances listed.
- CAA - Clean Air Act
 - CAA listed substances:
 - 1-methoxy-2-propanol is listed in CAA Section 112(b) - HON
 - 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether is listed in CAA Section 111, Section 112(b) - HON
 - 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve is listed in CAA Section 111, Section 112(b) - HAP.
- CWA - Clean Water Act
 - CWA listed substances:
 - None.

USA - State specific regulations

- California Proposition 65
 - Substance(s) listed under California Proposition 65:
 - None.
- Massachusetts Right to know
 - Substance(s) listed under Massachusetts Right to know:
 - 1-methoxy-2-propanol
 - 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.
- New Jersey Right to know
 - Substance(s) listed under New Jersey Right to know:
 - 1-methoxy-2-propanol
 - 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.
- Pennsylvania Right to know
 - Substance(s) listed under Pennsylvania Right to know:
 - 1-methoxy-2-propanol
 - 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.

16. OTHER INFORMATION

- Text of phrases referred to under heading 3:
 - H226 Flammable liquid and vapour.
 - H336 May cause drowsiness or dizziness.



Safety Data Sheet

Dark Walnut concentrated stain

H319 Causes serious eye irritation.
H315 Causes skin irritation.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H332 Harmful if inhaled.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.
H360 May damage fertility or the unborn child.
H335 May cause respiratory irritation.
H318 Causes serious eye damage.

Safety Data Sheet dated 10/2/2014, version 2

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

| | |
|-----------|--|
| ADR: | European Agreement concerning the International Carriage of Dangerous Goods by Road. |
| CAS: | Chemical Abstracts Service (division of the American Chemical Society). |
| CLP: | Classification, Labeling, Packaging. |
| DNEL: | Derived No Effect Level. |
| EINECS: | European Inventory of Existing Commercial Chemical Substances. |
| GHS: | Globally Harmonized System of Classification and Labeling of Chemicals. |
| HMIS: | Hazardous Materials Identification System |
| IARC: | International Agency for Research on Cancer |
| IATA: | International Air Transport Association. |
| IATA-DGR: | Dangerous Goods Regulation by the "International Air Transport Association" (IATA). |
| ICAO: | International Civil Aviation Organization. |
| ICAO-TI: | Technical Instructions by the "International Civil Aviation Organization" (ICAO). |
| IMDG: | International Maritime Code for Dangerous Goods. |
| INCI: | International Nomenclature of Cosmetic Ingredients. |
| KSt: | Explosion coefficient. |
| LC50: | Lethal concentration, for 50 percent of test population. |
| LD50: | Lethal dose, for 50 percent of test population. |
| LTE: | Long-term exposure. |
| NFPA: | National Fire Protection Association |
| NIOSH: | National Institute for Occupational Safety and Health |
| NTP: | National Toxicology Program |
| OSHA: | Occupational Safety and Health Administration |
| PNEC: | Predicted No Effect Concentration. |
| RID: | Regulation Concerning the International Transport of Dangerous Goods by Rail. |
| STE: | Short-term exposure. |
| STEL: | Short Term Exposure limit. |
| STOT: | Specific Target Organ Toxicity. |
| TLV: | Threshold Limiting Value. |
| TWATLV: | Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard). |