

PRODUCT: 6CW1S02
DESCRIPTION: Water Borne Hardener

CHEMICAL - PHYSICAL CHARACTERISTICS

SPECIFIC GRAVITY:	1.080 ± 0.010 (g/cc a 68° F)
DENSITY (WPG):	9.01 ± 0.010 (lbs/gal US at 68° F)
WEIGHT SOLIDS:	69% ± 1
VOLUME SOLIDS:	65.31% ± 1
VOC (material):	2.79 lbs/gal US or 334.80 g/l
VOC (coating):	2.79 lbs/gal US or 334.80 g/l
VOC Ratio:	0.45 lbs VOC/lbs Solids
HAPS Ratio:	0.00 lbs HAPS/lbs solids

This product meets U.S.A. TSCA regulations.

DSL Inventory: all the components are listed on the DSL inventory.

GENERAL PROPERTIES

This polyisocyanic hardener is for water borne 2k products. Do not use this hardener with temperatures below 15°C and with high relative humidity. This could influence drying times and stackability of your projects.

SHELF LIFE: 12 months.
Data refers to products preserved in original, sealed containers.

STORAGE: Keep in a fresh and well-ventilated place; do not exceed 77°-82.4° F.

Company Information: SIRCA S.p.A. has a quality system certified by DNV GL ISO 9001



The information supplied are correct to the best of our knowledge. However, as the coating process depends on many variables and the present application takes place without our supervision, we cannot assume any responsibility for the final result. Sirca guarantees that chemical and physical characteristics of the products are within the reported range. Due to the large variety of substrates and application devices, the purchaser/user should test our products in his own application conditions and safety and environment circumstances. Sirca's technical and sales departments are at customer's disposal for any further information regarding correct application of our products.