

**PRODUCT :** 6CWN100  
**DESCRIPTION:** Polyisocyanic hardener for water borne products

**CHEMICAL - PHYSICAL CHARACTERISTICS**

<b>SPECIFIC GRAVITY:</b>	1.11 ± 0.100 (Kg/l at 20°C)
<b>DENSITY (WPG):</b>	9.26 ± 0.100 (lbs/gal US at 68° F)
<b>WEIGHT SOLIDS:</b>	84% ± 1
<b>VOLUME SOLIDS:</b>	81.31% ± 1
<b>VOC (material):</b>	1.48 lbs/gal US or 177.70 g/l
<b>VOC (coating):</b>	1.48 lbs/gal US or 177.70 g/l
<b>VOC Ratio:</b>	0.19 lbs VOC/lbs Solids
<b>HAPS Ratio:</b>	0.00 lbs HAPS/lbs solids

**This product meets U.S.A. TSCA regulations.**

**GENERAL PROPERTIES**

Use of this polyisocyanate hardener will lead to increase in viscosity of the base. It is best to mix in small amounts and mix with fresh material.

Do not use this product with temperatures below 15°C and when relative humidity is high, since it will influence drying times and stackability.

For further information, please refer to our technical representatives.

**SHELF LIFE:** 1 year  
Data refers to product stored in original, sealed packing.

**STORAGE:** Keep in a cool, well ventilated place; temperature should not exceed 77°- 82.4° F.

**Company Information:** SIRCA S.p.A. has a quality system certified by DNV GL ISO 9001

◇◇◇◇◇◇◇◇◇◇

The information supplied are correct to the best of our knowledge. However, as the coating process depends on many variables and the present application takes place without our supervision, we cannot assume any responsibility for the final result. Sirca guarantees that chemical and physical characteristics of the products are within the reported range. Due to the large variety of substrates and application devices, the purchaser/user should test our products in his own application conditions and safety and environment circumstances. Sirca's technical and sales departments are at customer's disposal for any further information regarding correct application of our products.