

PRODUCT: 6ES100
DESCRIPTION: Oxidant solution
USE: Reactive Solution for Rust and Copper Special Effect.
APPLICATION SYSTEM: Traditional Spray Gun, Airless, Airmix

CHEMICAL - PHYSICAL CHARACTERISTICS

SPECIFIC GRAVITY: 1.034 ± 0.100 (Kg/l at 68°)
DENSITY (WPG): 8.63 ± 0.100 (lbs/gal US at 68° F)
WEIGHT SOLIDS: 10% ± 1
VOLUME SOLIDS: 7.5% ± 0.5
VOC (material): 0.00 lbs/gal US or 0.00 g/l
VOC (coating): 0.00 lbs/ga US or 0.00 g/l
VOC Ratio: 0 lbs VOC/lbs Solids
HAPS Ratio: 0 lbs HAPS/lbs solids

PREPARATION OF THE PRODUCT

6ES101 ready to use

This product meets U.S.A. TSCA regulations.

GENERAL PROPERTIES

Reactive solution for rust effect painting system.
Application: by spray or wipe.
Number of layers: 1 or more.
Touch free: 12 hours minimum

For further information, please refer to our technical representatives.

SHELF LIFE: 3 years.
Data refers to product stored in original, sealed packing.

STORAGE: Keep in a cool, well ventilated place; temperature should not exceed 77°- 82.4° F.

Company Information: SIRCA S.p.A. has a quality system certified by DNV GL ISO 9001



The information supplied are correct to the best of our knowledge. However, as the coating process depends on many variables and the present application takes place without our supervision, we cannot assume any responsibility for the final result. Sirca guarantees that chemical and physical characteristics of the products are within the reported range. Due to the large variety of substrates and application devices, the purchaser/user should test our products in his own application conditions and safety and environment circumstances. Sirca's technical and sales departments are at customer's disposal for any further information regarding correct application of our products.

