

PRODUCT: 6ES101
DESCRIPTION: Reductive solution
USE: Reactive Solution for Rust and Copper Special Effect
APPLICATION SYSTEM: Traditional Spray Gun, Airless, Airmix

CHEMICAL - PHYSICAL CHARACTERISTICS

SPECIFIC GRAVITY: 0.890 ± 0.100 (Kg/l at 68°)
DENSITY (WPG): 7.43 ± 0.100 (lbs/gal US at 68° F)
WEIGHT SOLIDS: 10% ± 1
VOLUME SOLIDS: 7.4% ± 0.5
VOC (material): 6.02 lbs/gal US or 720.90 g/l
VOC (coating): 6.70b/ga US or 802.36 g/l
VOC Ratio: 8.10 lbs VOC/lbs Solids
HAPS Ratio: 34.01 lbs HAPS/lbs solids

PREPARATION OF THE PRODUCT

6ES101 100 parts by weight
6CTN52 15 parts by weight
DPU820 / SOL-9054 20-30 parts by weight

Or

6ES101 100 parts by volume
6CTN52 15 parts by volume
DPU820 / SOL-9054 20-30 parts by volume

This product meets U.S.A. TSCA regulations.

GENERAL PROPERTIES

This additive stops the chemical reaction induced by 6ES100 (rust and copper special effect)

For further information, please refer to our technical representatives.

SHELF LIFE: 3 years
Data refers to product stored in original, sealed packing.

STORAGE: Keep in a cool, well ventilated place; temperature should not exceed 77°- 82.4° F.

Company Information: SIRCA S.p.A. has a quality system certified by DNV GL ISO 9001



The information supplied are correct to the best of our knowledge. However, as the coating process depends on many variables and the present application takes place without our supervision, we cannot assume any responsibility for the final result. Sirca guarantees that chemical and physical characteristics of the products are within the reported range. Due to the large variety of substrates and application devices, the purchaser/user should test our products in his own application conditions and safety and environment circumstances. Sirca's technical and sales departments are at customer's disposal for any further information regarding correct application of our products.

