

PRODUCT : FBU series
DESCRIPTION : Universal pigmented pastes for COLOUR PASSION system
USE : Tinting of pigmented sealers and topcoats

CHEMICAL - PHYSICAL CHARACTERISTICS

Code	Description	Vix at 25°C DIN Cup6	Specific weight g/cc at 25°C	Pack in Kg
FBU01	Oxide yellow universal paste	26" ± 5"	1,690 ± 0,030	5
FBU02	Orange universal paste	58" ± 5"	1,340 ± 0,030	3
FBU03	Oxide red universal paste	30" ± 5"	1,800 ± 0,030	3
FBU04	Violet oxide red universal paste	46" ± 5"	1,850 ± 0,030	5
FBU05	Blue universal paste	28" ± 5"	1,300 ± 0,030	3
FBU06	Green universal paste	31" ± 5"	1,280 ± 0,030	3
FBU07	Violet universal paste	45" ± 5"	1,070 ± 0,030	3
FBU08	White universal paste	30" ± 5"	1,990 ± 0,030	5
FBU09	Deep black universal paste	20" ± 5"	1,370 ± 0,030	3
FBU10	Cold yellow universal paste	19" ± 5"	1,840 ± 0,030	5
FBU11	Lemon yellow universal paste	Tixo	1,060 ± 0,030	3
FBU12	Golden yellow universal paste	32" ± 5"	1,320 ± 0,030	3
FBU13	Magenta universal paste	70" ± 5"	1,220 ± 0,030	3
FBU14	Scarlet red universal paste	29" ± 5"	1,290 ± 0,030	3
FBU15	Bright red universal paste	36" ± 5"	1,320 ± 0,030	3
FBU16	Black universal paste	15" ± 5"	1,230 ± 0,030	3

GENERAL FEATURES

This series of pastes can be used to tint the white and clear matt and high gloss bases, alkydic, nitro, acrylic and polyurethanic nature.

Every colour is characterised by a certain percentage of pastes, necessary to achieve the best results in terms of coverage and colour, please refer to the related formulary.

With this series can be prepared a wide variety of RAL, NCS, PANTONE, SIKKENS, etc. different colours.

SHELF LIFE: 12 months
 The data refers to products preserved in original, sealed containers.
STORAGE : Keep in a fresh and well ventilated place; do not exceed 25°-30°C.

Company Information: SIRCA S.p.A. has a quality system certified by DNV according to standard UNI EN ISO 9001



The information given in this technical sheet is based on the best of our knowledge and experience.

Sirca guarantees the consistency of the chemical/physical characteristics of its products within the tolerances indicated above.

The final result is the full responsibility of the user, who before using it must check that the product meets his requirements in terms of safety, application equipment, material to paint and environmental conditions.

Sirca's technical and commercial network is at your complete disposal to deal with any questions regarding how to correctly apply and use our products