



Safety Data Sheet

White WB 2K EXT INT Sealer

Safety Data Sheet dated 3/23/2020, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: White WB 2K EXT INT Sealer

Other means of identification:

Trade code: 6FWBP430

Recommended use of the chemical and restrictions on use

Recommended use: Surface coating

Restrictions on use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

Sirca S.p.A.

Address:

Viale Roma, 85
35010 S.Dono di Massanzago (PD) - ITALY
Tel. +39 0499322311

Distributed by:

GEMINI INDUSTRIES, INC.
2300 Holloway Drive
El Reno, OK 73036
USA
Tel. 1-800-262-5710
Fax 1-405-262-9310
www.gemini-coatings.com

Competent person responsible for the safety data sheet:

safety@sirca.it

Emergency phone number

For Hazardous Materials [or Dangerous Goods] Incident
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night
1-800-424-9300 / +1 703-527-3887.

2. HAZARD(S) IDENTIFICATION

Classification of the chemical



Warning, Carc. 2, Suspected of causing cancer.

Label elements

Hazard pictograms:



Warning

Hazard statements:

H351 Suspected of causing cancer.

Precautionary statements:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P405 Store locked up.
P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information



Safety Data Sheet

White WB 2K EXT INT Sealer

NFPA rating:



HMIS rating:

HEALTH	* 2
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 12.5% - < 20% Titanium dioxide

REACH No.: 01-2119489379-17-xxxx, CAS: 13463-67-7, EC: 236-675-5



A.6/2 Carc. 2 H351

>= 3% - < 5% Talc

CAS: 14807-96-6, EC: 238-877-9



A.1/4/Inhal Acute Tox. 4 H332



A.8/3 STOT SE 3 H335

>= 3% - < 5% 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether

REACH No.: 01-2119475104-44-xxxx, Index number: 603-096-00-8, CAS: 112-34-5, EC: 203-961-6



A.3/2A Eye Irrit. 2A H319

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None



Safety Data Sheet

White WB 2K EXT INT Sealer

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:

N.A.

Oxidizing properties:

N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature:

Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Titanium dioxide - CAS: 13463-67-7

ACGIH - TWA(8h): 10 mg/m³ - Notes: A4 - LRT irr

Talc - CAS: 14807-96-6

ACGIH - TWA(8h): 2 mg/m³ - Notes: Containing no asbestos fibers. (E,R), A4 - Pulm fibrosis, pulm func

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

(OEL (IT)) - TWA(8h): 67.5 mg/m³, 10 ppm - STEL: 101.2 mg/m³, 15 ppm - Behaviour: Binding

EU - TWA(8h): 67.5 mg/m³, 10 ppm - STEL: 101.2 mg/m³, 15 ppm

ACGIH - TWA(8h): 10 ppm - Notes: (IFV) - Hematologic, liver and kidney eff

DNEL Exposure Limit Values

Titanium dioxide - CAS: 13463-67-7

Worker Industry: 10 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Professional: 10 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 700 mg/kg/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

Worker Industry: 67.5 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Industry: 67.5 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 83 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects



Safety Data Sheet

White WB 2K EXT INT Sealer

Worker Industry: 101.2 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term (acute)
Consumer: 40.5 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Consumer: 60.7 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term (acute)
Consumer: 40.5 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
Consumer: 50 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Consumer: 5 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

Titanium dioxide - CAS: 13463-67-7

Target: Fresh Water - Value: 0.184 mg/l

Target: Marine water - Value: 0.0184 mg/l

Target: Soil (agricultural) - Value: 100 mg/kg

Target: Marine water sediments - Value: 100 mg/kg - Notes:: dry

Target: Freshwater sediments - Value: 1000 mg/kg - Notes:: dry

Target: Soil (agricultural) - Value: 100 mg/kg - Notes:: alimento

Target: orally (secondary poisoning) - Value: 1667 mg/kg

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

Target: Fresh Water - Value: 1 mg/l

Target: Marine water - Value: 0.1 mg/l

Target: occasional emission - Value: 3.9 mg/l

Target: STP - Value: 200 mg/l

Target: Freshwater sediments - Value: 4 mg/kg dwt

Target: Marine water sediments - Value: 0.4 mg/kg dwt

Target: Soil (agricultural) - Value: 0.4 mg/kg dwt

Target: orally (secondary poisoning) - Value: 56 mg/kg

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:	liquid
Odour:	characteristic
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	< 1° C
Initial boiling point and boiling range:	> 55° C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	other >=55°C (>= 131°F)
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	1.3700 Kg/l a 20°C
Solubility in water:	N.A.
Solubility in oil:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Auto-ignition temperature:	> 250° C
Decomposition temperature:	N.A.
Viscosity (typical value):	18000.00 cPs Brookfield
Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

No dangerous reaction is stored and used appropriately.



Safety Data Sheet

White WB 2K EXT INT Sealer

Conditions to avoid
Stable under normal conditions.
Incompatible materials
None in particular.
Hazardous decomposition products
None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects
Toxicological information of the product:
N.A.

Toxicological information of the main substances found in the product:

Titanium dioxide - CAS: 13463-67-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 6.82 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

b) skin corrosion/irritation:

Test: Eye Irritant - Species: Rabbit No

Test: Skin Irritant - Species: Rabbit No

d) respiratory or skin sensitisation:

Test: Skin Sensitization - Species: Mouse No

i) STOT-repeated exposure:

Test: NOAEL - Species: Rat 3500 mg/kg/day - Source: polmoni

Talc - CAS: 14807-96-6

a) acute toxicity:

Test: LD50 - Route: Oral > 5000 mg/kg body weight

b) skin corrosion/irritation:

Test: Skin Irritant No

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rabbit = 3 mg/l - Duration: 2h

Test: LD50 - Route: Oral - Species: Rat = 5660 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 2700 mg/kg

Test: LD50 - Route: Oral - Species: Mouse = 2400 mg/kg

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

Titanium dioxide - Group 2B

Talc - Group 3.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

Titanium dioxide - CAS: 13463-67-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 61 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia > 1000 mg/l - Duration h: 48

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae 100000 mg/kg - Duration h: 480

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 1300 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 100 mg/l - Duration h: 48

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

None

13. DISPOSAL CONSIDERATIONS

6FWBP430/1

Page n. 5 of 7



Safety Data Sheet

White WB 2K EXT INT Sealer

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

UN number
Not classified as dangerous in the meaning of transport regulations.

UN proper shipping name
N.A.

Transport hazard class(es)
N.A.

Packing group
N.A.

Environmental hazards
N.A.

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)
No

Special precautions
N.A.

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act
TSCA inventory: all the components are listed on the TSCA inventory.
TSCA listed substances:
None.

SARA - Superfund Amendments and Reauthorization Act
Section 302 – Extremely Hazardous Substances: no substances listed.
Section 304 – Hazardous substances: no substances listed.
Section 313 – Toxic chemical list: no substances listed.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
No substances listed.

CAA - Clean Air Act
CAA listed substances:
2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether is listed in CAA Section 111, Section 112(b) - HON.

CWA - Clean Water Act
CWA listed substances:
None.

USA - State specific regulations

California Proposition 65
Substance(s) listed under California Proposition 65:
Titanium Dioxide (airborne, unbound particles of respirable size) is known to the state of California to cause cancer. This listing does not cover titanium dioxide when it remains bound within a product matrix

Massachusetts Right to know
Substance(s) listed under Massachusetts Right to know:
Titanium dioxide.

New Jersey Right to know
Substance(s) listed under New Jersey Right to know:
Titanium dioxide
Talc.

Pennsylvania Right to know
Substance(s) listed under Pennsylvania Right to know:
Titanium dioxide
Talc.

16. OTHER INFORMATION

Text of phrases referred to under heading 3:
H351 Suspected of causing cancer.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H319 Causes serious eye irritation.

Safety Data Sheet dated 3/23/2020, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.



Safety Data Sheet

White WB 2K EXT INT Sealer

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average