



## Safety Data Sheet

### Clear ACR Self sealer

Safety Data Sheet dated 1/15/2020, version 1

#### 1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: Clear ACR Self sealer

Other means of identification:

Trade code: 6OTA178G10

Recommended use of the chemical and restrictions on use

Recommended use: Surface coating

Restrictions on use:

---

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

Sirca S.p.A.

Address:

Viale Roma, 85  
35010 S. Dono di Massanzago (PD) - ITALY  
Tel. +39 0499322311

Distributed by:

GEMINI INDUSTRIES, INC.  
2300 Holloway Drive  
El Reno, OK 73036  
USA  
Tel. 1-800-262-5710  
Fax 1-405-262-9310  
www.gemini-coatings.com

Competent person responsible for the safety data sheet:

safety@sirca.it

Emergency phone number

For Hazardous Materials [or Dangerous Goods] Incident  
Spill, Leak, Fire, Exposure, or Accident  
Call CHEMTREC Day or Night  
1-800-424-9300 / +1 703-527-3887.

#### 2. HAZARD(S) IDENTIFICATION

Classification of the chemical



Danger, Flam. Liq. 2, Highly flammable liquid and vapour.



Warning, Skin Irrit. 2, Causes skin irritation.



Warning, Eye Irrit. 2A, Causes serious eye irritation.



Warning, Skin Sens. 1A, May cause an allergic skin reaction.



Warning, Carc. 2, Suspected of causing cancer.



Warning, Repr. 2, Suspected of damaging fertility or the unborn child.



Warning, STOT SE 3, May cause respiratory irritation.



Warning, STOT SE 3, May cause drowsiness or dizziness.



Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

## Safety Data Sheet

### Clear ACR Self sealer

Label elements

Hazard pictograms:



Danger

Hazard statements:

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash your face, hands and every exposed part thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 IF ON SKIN: Wash with plenty of water and soap.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER/doctor/... if you feel unwell.
- P314 Get medical advice/attention if you feel unwell.
- P321 Specific treatment (see supplementary instructions on this label).
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use a CO<sub>2</sub>, Foam, Chemical powders for extinction.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information

NFPA rating:





## Safety Data Sheet Clear ACR Self sealer

HMIS rating:

HEALTH	* 2
FLAMMABILITY	3
PHYSICAL HAZARD	1
PERSONAL PROTECTION	

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 20% - < 25% n-butyl acetate

REACH No.: 01-2119485493-29-xxxx, Index number: 607-025-00-1, CAS: 123-86-4, EC: 204-658-1



B.6/3 Flam. Liq. 3 H226



A.8/3 STOT SE 3 H336

>= 20% - < 25% xylene [isomer mixture]

REACH No.: 01-2119488216-32-xxxx, Index number: 601-022-00-9, CAS: 1330-20-7, EC: 215-535-7



B.6/3 Flam. Liq. 3 H226



A.10/1 Asp. Tox. 1 H304



A.3/2A Eye Irrit. 2A H319



A.8/3 STOT SE 3 H335



A.9/2 STOT RE 2 H373



A.2/2 Skin Irrit. 2 H315



A.1/4/Dermal Acute Tox. 4 H312



A.1/4/Inhal Acute Tox. 4 H332

>= 12.5% - < 20% ethyl acetate

REACH No.: 01-2119475103-46-xxxx, Index number: 607-022-00-5, CAS: 141-78-6, EC: 205-500-4



B.6/2 Flam. Liq. 2 H225



A.3/2A Eye Irrit. 2A H319



A.8/3 STOT SE 3 H336

## Safety Data Sheet

### Clear ACR Self sealer

>= 3% - < 5% ethylbenzene

REACH No.: 01-2119489370-35-xxxx, Index number: 601-023-00-4, CAS: 100-41-4, EC: 202-849-4



A.10/1 Asp. Tox. 1 H304



B.6/2 Flam. Liq. 2 H225



A.2/2 Skin Irrit. 2 H315



A.1/4/Inhal Acute Tox. 4 H332



A.6/2 Carc. 2 H351

>= 3% - < 5% toluene

REACH No.: 01-2119471310-51-xxxx, Index number: 601-021-00-3, CAS: 108-88-3, EC: 203-625-9



B.6/2 Flam. Liq. 2 H225



A.7/2 Repr. 2 H361



A.10/1 Asp. Tox. 1 H304



A.9/2 STOT RE 2 H373



A.2/2 Skin Irrit. 2 H315



A.8/3 STOT SE 3 H336

>= 0.2% - < 0.25% methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate

REACH No.: 01-2119452498-28-xxxx, Index number: 607-035-00-6, CAS: 80-62-6, EC: 201-297-1



B.6/2 Flam. Liq. 2 H225



A.8/3 STOT SE 3 H335



A.2/2 Skin Irrit. 2 H315



A.4.2/1 Skin Sens. 1 H317

>= 0.1% - < 0.2% Poly(oxy-1,2-ethanediyl),

alpha-[3-[3-(2h-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-omega-hydroxy-]-

CAS: 104810-48-2



A.4.2/1A Skin Sens. 1A H317

US-HAE/A2 Aquatic Acute 2 H401



US-HAE/C2 Aquatic Chronic 2 H411

#### 4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.



## Safety Data Sheet

### Clear ACR Self sealer

In case of eyes contact:  
After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.  
Protect uninjured eye.

In case of Ingestion:  
Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:  
In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed  
None

Indication of immediate medical attention and special treatment needed  
In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:  
None

---

#### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:  
In case of fire: Use a CO<sub>2</sub>, Foam, Chemical powders for extinction.

Unsuitable extinguishing media:  
None in particular.

Specific hazards arising from the chemical  
Do not inhale explosion and combustion gases.  
Burning produces heavy smoke.

Hazardous combustion products:  
None

Explosive properties: N.A.  
Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters  
Use suitable breathing apparatus .  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Move undamaged containers from immediate hazard area if it can be done safely.

---

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures  
Wear personal protection equipment.  
Remove all sources of ignition.  
Wear breathing apparatus if exposed to vapours/dusts/aerosols.  
Provide adequate ventilation.  
Use appropriate respiratory protection.  
See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up  
Wash with plenty of water.

---

#### 7. HANDLING AND STORAGE

Precautions for safe handling  
Avoid contact with skin and eyes, inhalation of vapours and mists.  
Exercise the greatest care when handling or opening the container.  
Do not use on extensive surface areas in premises where there are occupants.  
Use localized ventilation system.  
Don't use empty container before they have been cleaned.  
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.  
Contaminated clothing should be changed before entering eating areas.  
Do not eat or drink while working.  
See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities  
Always keep in a well ventilated place.  
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.  
Keep away from flame and sparks. Avoid accumulating electrostatic charge.  
Place recipients on the ground whilst decanting, and wear anti-static clothing and shoes.

Keep away from food, drink and feed.  
Incompatible materials:  
None in particular.  
Instructions as regards storage premises:  
Cool and adequately ventilated.  
Safety electric system.  
Storage temperature:  
Store at ambient temperature.



## Safety Data Sheet

### Clear ACR Self sealer

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

##### Control parameters

- n-butyl acetate - CAS: 123-86-4
  - TWA (Italia) - TWA: 150 ppm - STEL: 200 ppm
  - ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr
- xylene [isomer mixture] - CAS: 1330-20-7
  - (OEL (IT)) - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Behaviour: Binding - Notes: pelle
  - EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Skin
  - ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair
- ethyl acetate - CAS: 141-78-6
  - (OEL (IT)) - TWA: 734 mg/m<sup>3</sup>, 200 ppm - STEL: 1469 mg/m<sup>3</sup>, 400 ppm
  - ACGIH - TWA(8h): 400 ppm - Notes: URT and eye irr
  - EU - TWA(8h): 734 mg/m<sup>3</sup>, 200 ppm - STEL: 1468 mg/m<sup>3</sup>, 400 ppm
- ethylbenzene - CAS: 100-41-4
  - (OEL (IT)) - TWA(8h): 442 mg/m<sup>3</sup>, 100 ppm - STEL: 884 mg/m<sup>3</sup>, 200 ppm - Behaviour: Binding - Notes: pelle
  - EU - TWA(8h): 442 mg/m<sup>3</sup>, 100 ppm - STEL: 884 mg/m<sup>3</sup>, 200 ppm - Notes: Skin
  - ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair
- toluene - CAS: 108-88-3
  - (OEL (IT)) - TWA(8h): 192 mg/m<sup>3</sup>, 50 ppm - Behaviour: Binding - Notes: Pelle
  - EU - TWA(8h): 192 mg/m<sup>3</sup>, 50 ppm - STEL: 384 mg/m<sup>3</sup>, 100 ppm - Notes: Skin
  - ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - Visual impair, female repro, pregnancy loss
- methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate - CAS: 80-62-6
  - (OEL (IT)) - TWA(8h): 50 ppm - STEL: 100 ppm - Behaviour: Binding
  - EU - TWA(8h): 50 ppm - STEL: 100 ppm
  - ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: DSEN, A4 - URT and eye irr, body weight eff, pulm edema

##### DNEL Exposure Limit Values

- n-butyl acetate - CAS: 123-86-4
  - Worker Professional: 600 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects
  - Worker Professional: 300 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects
  - Worker Professional: 11 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Worker Professional: 11 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects
  - Consumer: 300 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, local effects
  - Consumer: 35.7 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects
  - Consumer: 6 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects
  - Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
  - Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects
- xylene [isomer mixture] - CAS: 1330-20-7
  - Worker Industry: 180 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Worker Industry: 77 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
  - Consumer: 108 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Consumer: 1872 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects
  - Consumer: 12.5 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects
- ethyl acetate - CAS: 141-78-6
  - Worker Industry: 1468 mg/m<sup>3</sup> - Consumer: 734 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
  - Worker Industry: 1468 ppm - Exposure: Human Inhalation - Frequency: Short Term (acute)
  - Worker Industry: 63 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Worker Industry: 734 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects
  - Worker Industry: 734 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
  - Consumer: 4.5 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects
  - Consumer: 734 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term (acute)
  - Consumer: 734 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
  - Consumer: 37 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, local effects
  - Consumer: 367 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects
  - Consumer: 367 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
- ethylbenzene - CAS: 100-41-4
  - Worker Industry: 180 mg/kg/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Worker Industry: 293 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects
  - Worker Industry: 77 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
- toluene - CAS: 108-88-3
  - Consumer: 226 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
  - Consumer: 226 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects
  - Consumer: 226 mg/m<sup>3</sup> - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Consumer: 56.5 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
  - Consumer: 8.13 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects
  - Worker Industry: 384 mg/kg/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Worker Industry: 384 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
  - Worker Industry: 192 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
- methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate - CAS: 80-62-6
  - Worker Industry: 210 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects
  - Worker Industry: 1.5 mg/cm<sup>2</sup> - Exposure: Human Dermal - Frequency: Long Term, local effects



## Safety Data Sheet

### Clear ACR Self sealer

Worker Industry: 210 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
Worker Industry: 13.67 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
Worker Industry: 1.5 mg/cm<sup>2</sup> - Exposure: Human Dermal - Frequency: Short Term, local effects  
Consumer: 74.3 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
Consumer: 105 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects  
Consumer: 1.5 mg/cm<sup>2</sup> - Exposure: Human Dermal - Frequency: Short Term, local effects  
Consumer: 8.2 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

#### PNEC Exposure Limit Values

n-butyl acetate - CAS: 123-86-4

Target: Fresh Water - Value: 0.18 mg/l  
Target: Marine water - Value: 0.018 mg/l  
Target: Freshwater sediments - Value: 0.981 mg/kg  
Target: Marine water sediments - Value: 0.0981 mg/kg  
Target: Soil (agricultural) - Value: 0.0903 mg/kg  
Target: STP - Value: 35.6 mg/l

xylene [isomer mixture] - CAS: 1330-20-7

Target: Fresh Water - Value: 0.327 mg/l  
Target: Fresh Water - Value: 0.327 mg/l  
Target: occasional emission - Value: 0.327 mg/l  
Target: Microorganisms in sewage treatments - Value: 6.58 mg/l  
Target: Soil (agricultural) - Value: 2.31 mg/kg - Notes:: dry  
Target: Marine water sediments - Value: 12.46 mg/kg - Notes:: dry  
Target: Freshwater sediments - Value: 12.46 mg/kg - Notes:: dry

ethyl acetate - CAS: 141-78-6

Target: Fresh Water - Value: 0.26 mg/l  
Target: Marine water - Value: 0.026 mg/l  
Target: Freshwater sediments - Value: 1.25 mg/kg  
Target: Marine water sediments - Value: 0.125 mg/kg  
Target: Soil (agricultural) - Value: 0.24 mg/kg  
Target: orally (secondary poisoning) - Value: 200 mg/kg - Notes:: Dietetico  
Target: STP - Value: 650 mg/l

ethylbenzene - CAS: 100-41-4

Target: Fresh Water - Value: 0.1 mg/l  
Target: Marine water - Value: 0.01 mg/l  
Target: Marine water sediments - Value: 13.7 mg/l  
Target: Freshwater sediments - Value: 13.7 mg/l  
Target: occasional emission - Value: 0.1 mg/l

toluene - CAS: 108-88-3

Target: Fresh Water - Value: 0.68 mg/l  
Target: Marine water - Value: 0.68 mg/l  
Target: Soil (agricultural) - Value: 2.89 mg/kg  
Target: Marine water sediments - Value: 16.39 mg/l  
Target: Freshwater sediments - Value: 16.39 mg/l  
Target: STP - Value: 13.61 mg/l

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate - CAS: 80-62-6

Target: Fresh Water - Value: 0.94 mg/l  
Target: Marine water - Value: 0.094 mg/l  
Target: Freshwater sediments - Value: 5.74 mg/kg  
Target: Soil (agricultural) - Value: 1.47 mg/kg  
Target: occasional emission - Value: 0.94 mg/l  
Target: Microorganisms in sewage treatments - Value: 10 mg/l

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Use adequate protective respiratory equipment.

Thermal Hazards:

None

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:	liquid
Odour:	characteristic
Odour threshold:	N.A.
pH:	N.A.



## Safety Data Sheet

### Clear ACR Self sealer

Melting point / freezing point:	< 1° C
Initial boiling point and boiling range:	> 55° C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	< 21°C - < 69.8 °F
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	0.9200 Kg/l a 20°C
Solubility in water:	N.A.
Solubility in oil:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Auto-ignition temperature:	> 250° C
Decomposition temperature:	N.A.
Viscosity (typical value):	30.00 " Din cup # 4
Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

## 10. STABILITY AND REACTIVITY

Reactivity	It may generate dangerous reactions (See subsections below)
Chemical stability	It may generate dangerous reactions (See subsections below)
Possibility of hazardous reactions	No dangerous reaction is stored and used appropriately.
Conditions to avoid	Avoid accumulating electrostatic charge. Vapours can form explosive mixtures with air.
Incompatible materials	Avoid contact with combustible materials. The product could catch fire.
Hazardous decomposition products	None.

## 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects	Toxicological information of the product: N.A.
Toxicological information of the main substances found in the product:	n-butyl acetate - CAS: 123-86-4 a) acute toxicity: Test: LC50 - Route: Inhalation - Species: Rat > 21 mg/l - Duration: 4h Test: LD50 - Route: Oral - Species: Rat = 10736 mg/kg - Notes: Method OECD linee guide 402 Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg xylene [isomer mixture] - CAS: 1330-20-7 a) acute toxicity: Test: LD50 - Route: Inhalation - Species: Rat = 27 mg/l - Duration: 4h Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg Test: LD50 - Route: Skin - Species: Rabbit = 12126 mg/kg ethyl acetate - CAS: 141-78-6 a) acute toxicity: Test: LD50 - Route: Skin - Species: Rabbit > 20000 mg/kg Test: LD50 - Route: Oral - Species: Rat = 5620 mg/kg Test: LC50 - Route: Inhalation - Species: Rat > 29.3 mg/l - Duration: 4h Test: LD50 - Route: Oral - Species: Rabbit = 4934 mg/kg body weight b) skin corrosion/irritation: Test: Skin Irritant - Route: Skin - Species: Rabbit Negative e) germ cell mutagenicity: Test: Genotoxicity Negative j) aspiration hazard: Test: Respiratory Tract Corrosive - Route: Inhalation Positive ethylbenzene - CAS: 100-41-4 a) acute toxicity: Test: LD50 - Route: Skin - Species: Rabbit = 15400 mg/kg Test: LC50 - Route: Inhalation - Species: Rat = 4000 Ppm - Duration: 4h d) respiratory or skin sensitisation: Test: Skin Sensitization - Route: Skin - Species: Cavia porcellus Negative toluene - CAS: 108-88-3 a) acute toxicity:





## Safety Data Sheet

### Clear ACR Self sealer

Test: LD50 - Route: Oral - Species: Rat 5000 mg/kg - Duration: 24h  
Test: LD50 - Route: Skin - Species: Rabbit 12267 mg/kg  
Test: LC50 - Route: Inhalation - Species: Rat 25.7 mg/l - Duration: 4h  
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate - CAS: 80-62-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 7900 mg/kg  
Test: LC50 - Route: Inhalation - Species: Rat = 29.8 mg/l - Duration: 4h  
Test: LD50 - Route: Skin - Species: Rabbit = 5000 mg/kg

Poly(oxy-1,2-ethanediyl), alpha-[3-[3-(2h-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-omega-hydroxy-]- - CAS: 104810-48-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: (OECD Guideline 401) - Notes: No mortality was observed  
Test: LC0 - Route: Inhalation - Species: Rat > 5.8 mg/l - Duration: 14 d - Notes: No mortality was observed  
Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg - Source: (OECD Guideline 402) - Notes: No mortality was observed

b) skin corrosion/irritation:

Test: Skin Irritant - Species: Rabbit Negative - Source: (OECD Guideline 405) - Notes: Assessment of irritating effects: may cause slight irritation to the skin.

c) serious eye damage/irritation:

Test: Eye Irritant - Species: Rabbit Negative - Source: (OECD Guideline 404) - Notes: Assessment of irritating effects: May cause slight irritation to the eyes

d) respiratory or skin sensitisation:

Test: Skin Sensitization - Species: Cavia porcellus Positive - Source: (OECD Guideline 405)

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

xylene [isomer mixture] - Group 3  
ethylbenzene - Group 2B  
toluene - Group 3  
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate - Group 3.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 64 mg/l - Duration h: 48  
Endpoint: EC50 - Species: Daphnia = 73 mg/l - Duration h: 24  
Endpoint: EC50 - Species: Algae = 674 mg/l - Duration h: 72

xylene [isomer mixture] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 48  
Endpoint: LC50 - Species: Fish = 3.2 mg/l - Duration h: 96  
Endpoint: LC50 - Species: Algae = 2.6 mg/l - Duration h: 73

ethyl acetate - CAS: 141-78-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 454.7 mg/l - Duration h: 96  
Endpoint: EC50 - Species: Daphnia = 154 mg/l - Duration h: 48  
Endpoint: EC50 - Species: Algae = 3300 mg/l - Duration h: 48

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae > 100 mg/l - Duration h: 72

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 42.3 mg/l - Duration h: 96

toluene - CAS: 108-88-3

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 5.5 ml/l - Duration h: 96  
Endpoint: EC50 - Species: Algae > 134 ml/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: EC50 - Species: Daphnia = 3.78 mg/l - Duration h: 48

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate - CAS: 80-62-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 191 mg/l - Duration h: 96  
Endpoint: EC50 - Species: Daphnia = 69 mg/l - Duration h: 48  
Endpoint: EC50 - Species: Algae > 110 mg/l - Duration h: 72

Poly(oxy-1,2-ethanediyl), alpha-[3-[3-(2h-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-omega-hydroxy-]- - CAS: 104810-48-2



## Safety Data Sheet

### Clear ACR Self sealer

- a) Aquatic acute toxicity:  
Species: Daphnia = 1 mg/l - Notes: 21 d
- Persistence and degradability  
N.A.
- Bioaccumulative potential  
N.A.
- Mobility in soil  
N.A.
- Other adverse effects  
None

---

### 13. DISPOSAL CONSIDERATIONS

- Waste treatment and disposal methods  
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

---

### 14. TRANSPORT INFORMATION

- UN number  
ADR-UN Number: 1263  
DOT-UN Number: 1263  
IATA-UN Number: 1263  
IMDG-UN Number: 1263
- UN proper shipping name  
ADR-Shipping Name: Paint Related material  
DOT-Shipping Name: Paint Related material  
IATA-Shipping Name: Paint Related material  
IMDG-Shipping Name: Paint Related material
- Transport hazard class(es)  
ADR-Class: 3  
DOT-Class: 3  
IATA-Class: 3  
IMDG-Class: 3
- Packing group  
ADR-Packing Group: II  
DOT-Packing Group: II  
IATA-Packing group: II  
IMDG-Packing group: II
- Environmental hazards  
ADR-Environmental Pollutant: No  
IMDG-Marine pollutant: No
- Special precautions  
ADR-Tunnel Restriction Code: D/E  
DOT-Special provisions: 149, B52, IB2, T4, TP1, TP8, TP28  
IATA-Passenger Aircraft: 353  
IATA-Cargo Aircraft: 364  
IATA-S.P.: A72  
IATA-ERG: 8L  
IMDG-EmS: F-E, S-E  
IMDG-Storage category: B
- Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)  
No

---

### 15. REGULATORY INFORMATION

- USA - Federal regulations
  - TSCA - Toxic Substances Control Act  
TSCA inventory: all the components are listed on the TSCA inventory.  
TSCA listed substances:  
n-butyl acetate is listed in TSCA Section 4, Section 12b  
ethylbenzene is listed in TSCA Section 4  
toluene is listed in TSCA Section 8a - CAIR  
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate is listed in TSCA Section 4.
  - SARA - Superfund Amendments and Reauthorization Act  
Section 302 – Extremely Hazardous Substances: no substances listed.  
Section 304 – Hazardous substances: no substances listed.  
Section 313 – Toxic chemical list: xylene [isomer mixture], ethylbenzene, toluene, methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate.
  - CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act  
Substance(s) listed under CERCLA: n-butyl acetate - Reportable quantity: 5000 pounds  
xylene [isomer mixture] - Reportable quantity: 100 pounds  
ethyl acetate - Reportable quantity: 5000 pounds



## Safety Data Sheet

### Clear ACR Self sealer

ethylbenzene - Reportable quantity: 1000 pounds  
toluene - Reportable quantity: 1000 pounds  
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate - Reportable quantity: 1000 pounds.  
Reportable quantity for mixture: 445.8821667 pounds.

#### CAA - Clean Air Act

CAA listed substances:

n-butyl acetate is listed in CAA Section 111

xylene [isomer mixture] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

ethyl acetate is listed in CAA Section 111

ethylbenzene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

toluene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

#### CWA - Clean Water Act

CWA listed substances:

n-butyl acetate is listed in CWA Section 311, Section 304

xylene [isomer mixture] is listed in CWA Section 311, Section 304

ethyl acetate is listed in CWA Section 304

ethylbenzene is listed in CWA Section 311, Section 304, Section 307

toluene is listed in CWA Section 311, Section 304, Section 307

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate is listed in CWA Section 311.

#### USA - State specific regulations

##### California Proposition 65

Substance(s) listed under California Proposition 65:

ethylbenzene - Listed as carcinogen

toluene - Listed as reproductive toxicant.

##### Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

n-butyl acetate

xylene [isomer mixture]

ethyl acetate

ethylbenzene

toluene

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate.

##### New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

n-butyl acetate

xylene [isomer mixture]

ethyl acetate

ethylbenzene

toluene

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate.

##### Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

n-butyl acetate

xylene [isomer mixture]

ethyl acetate

ethylbenzene

toluene

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate.

---

## 16. OTHER INFORMATION

Text of phrases referred to under heading 3:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H315 Causes skin irritation.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H225 Highly flammable liquid and vapour.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H317 May cause an allergic skin reaction.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Safety Data Sheet dated 1/15/2020, version 1



## Safety Data Sheet

### Clear ACR Self sealer

**Disclaimer:**

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average