



# SAFETY DATA SHEET

## SECTION 1 - Chemical Product and Company Information

Product Name: SLOW REDUCER (1G) Product Code: DPU530-1

Manufactured by:  
**Gemini Coatings**  
2300 Holloway Drive  
El Reno, OK 73036  
800-262-5710

**24- Hour Emergency (Spill, Leak, Exposure or Accident):**  
**INFOTRAC 800-535-5053**  
**Outside USA, Call Collect 1-352-323-3500**

**24- Hour Emergency HAZMAT Response and MSDS Help:**  
**EMI 800-510-8510**

Product Use: A protective and/or decorative finish or accompanying product (reference label or product data sheet for more information).

Not recommended for: Any other use not detailed on product data sheet or label.

## SECTION 2 - Hazards Identification

### GHS Ratings:

Flammable liquid 3

Skin corrosive 3

Eye corrosive 2B

Flash point  $\geq 23^{\circ}\text{C}$  and  $\leq 60^{\circ}\text{C}$  (140°F)

Reversible adverse effects in dermal tissue, Draize score:  
 $\geq 1.5 < 2.3$

Mild eye irritant: Subcategory 2B, Reversible in 7 days

### GHS Hazards

H226 Flammable liquid and vapour  
H316 Causes mild skin irritation  
H320 Causes eye irritation

### GHS Precautions

P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking  
P233 Keep container tightly closed  
P240 Ground/bond container and receiving equipment  
P241 Use explosion-proof electrical/ventilating/light/mixers/equipment  
P242 Use only non-sparking tools  
P243 Take precautionary measures against static discharge  
P264 Wash any exposed skin thoroughly after handling  
P280 Wear protective gloves/protective clothing/eye protection/face protection  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing  
P332+P313 If skin irritation occurs: Get medical advice/attention  
P337+P313 Get medical advice/attention  
P370+P378 In case of fire: Use the NFPA Class B extinguisher for extinction  
P403+P235 Store in a well ventilated place. Keep cool

**Signal Word: Warning****SECTION 3 - Composition/Information on Ingredients**

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
n-Butyl acetate 123-86-4 62%	150 ppm TWA; 710 mg/m <sup>3</sup> TWA	150 ppm STEL (listed under Butyl acetates, all isomers) 50 ppm TWA (listed under Butyl acetates, all isomers)	NIOSH: 150 ppm TWA; 710 mg/m <sup>3</sup> TWA 200 ppm STEL; 950 mg/m <sup>3</sup> STEL
Propylene glycol monomethyl ether acetate 108-65-6 38%			

**SECTION 4 - First Aid Measures****Inhalation:**

Remove exposed individual to fresh air and assist breathing if necessary. Seek medical attention.

**Eye Contact:**

Flush eyes with lukewarm water for 15 minutes. Seek medical attention immediately.

**Skin:**

Remove contaminated clothing, wash area immediately with soap and water. See physician if irritation persists.

**Ingestion:**

Rinse mouth out immediately. Drink 1 or 2 glasses of water to dilute. DO NOT induce vomiting. Contact physician or poison control center immediately.

**SECTION 5 - Fire Fighting Measures**

Alcohol Foam, CO<sub>2</sub>, Dry Chemical

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat. Do not apply to hot surfaces. Never use welding or cutting torch on or near container (even empty) because product (even residue) may ignite explosively. Liquid and vapor states of this substance are dangerous fire hazards and moderate explosion hazards when exposed to heat or flame.

Oxidation may produce carbon and nitrogen oxides.

Clear fire area of unprotected personnel. Do not enter confined space without helmet, face shield, bunker coat, gloves, rubber boots and a positive pressure NIOSH-approved self-contained breathing apparatus. A water stream can scatter flames. A spray of water may be used to cool closed containers to prevent pressure buildup and possible auto ignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable. The National Fire Protection Association Class B extinguisher is designed to extinguish NFPA Class IB flammable liquid fires.

**SECTION 6 - Accidental Release Measures**

Stay upwind and away from spill or leak unless wearing appropriate protective equipment. Stop and/or contain discharge if it may be done safely. Keep all sources of ignition away. Ventilate area of spill. Use non-sparking tools for clean up. Cover with inert material to reduce fumes. Keep out of drains, sewer or waterways.

If large spill occurs, alert spill response teams. Contact fire authorities. Notify local health and pollution control

agencies.

### SECTION 7- Handling and Storage

#### Handling:

Bond and ground metal containers when transferring liquid. Avoid free fall of liquid in excess of a few inches. Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected skin areas with water. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this sheet must be observed.

#### Storage:

Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. DO NOT SMOKE in or near storage areas.

### SECTION 8 - Exposure Controls/Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
n-Butyl acetate 123-86-4	150 ppm TWA; 710 mg/m3 TWA	150 ppm STEL (listed under Butyl acetates, all isomers) 50 ppm TWA (listed under Butyl acetates, all isomers)	NIOSH: 150 ppm TWA; 710 mg/m3 TWA 200 ppm STEL; 950 mg/m3 STEL
Propylene glycol monomethyl ether acetate 108-65-6			

Use local exhaust as required to control vapor concentrations.  
Avoid prolonged or repeated breathing of vapors.

#### Respiratory Protection:

If exposure exceeds TLV or PELs, use NIOSH approved respirator to prevent overexposure.

#### Skin Protection:

Required for prolonged or repeated contact. Wear resistant gloves such as natural rubber, neoprene, buna N or nitrile. An apron should be worn to avoid skin contact.

#### Eye Protection:

Wear splash proof goggles and face shield if there is a likelihood of contact with eyes.

#### Hygienic Practices

Wash hands thoroughly before eating or using the restroom. Remove contaminated clothing immediately and do not wear again until it has been properly laundered.

### SECTION 9 - Physical and Chemical Properties

<b>Vapor Density</b> Heavier Than Air	<b>Evaporation Rate</b> Faster than Butyl Acetate
<b>Boiling range:</b> 126°C	<b>Melting point:</b> N/A
<b>Freezing point:</b> N/A	<b>Flash point:</b> 81°F, 27°C
<b>Flammability:</b> N/A	<b>Explosive Limits:</b> N/A
<b>Autoignition temperature:</b> 315°C	<b>Decomposition temperature:</b> N/A
<b>Relative Density:</b> N/A	<b>Vapor Pressure</b> N/A
<b>Odor threshold:</b> N/A	<b>pH:</b> N/A
<b>SPECIFIC GRAVITY</b> 0.9144	<b>Solubility:</b> N/A
<b>Partition coefficient (n- N/A octanol/water):</b>	<b>Viscosity:</b> N/A

<b>Grams VOC less water:</b> N/A <b>% WT. VOLATILE (VOC)</b> 100.0000 <b>Lbs VOC/Gallon Solids</b> 0.0000 <b>SOLIDS VOL%</b> 0.0000 <b>SPREAD @ 1 MIL</b> 0.0000 <b>Appearance</b> Clear Liquid <b>Physical State</b> Liquid <b>Coating VOC (g/l)</b> 912.3950 <b>Coating VOC (Lb/GI)</b> 7.6141	<b>% VOLUME VOLATILE (VOC)</b> 100.0000 <b>% Pig. by wt.</b> 0.0000 <b>VOLATILE WT%</b> 100.0000 <b>DENSITY (Lb/Gal)</b> 7.6141 <b>HAPS (lbs/gI)</b> 0.0000 <b>Odor</b> N/A <b>Material VOC (g/l)</b> 912.3950 <b>Material VOC (Lb/GI)</b> 7.6141
--	--

**SECTION 10 - Stability and Reactivity**

**Stability:** Stable under normal conditions.

**Materials to Avoid:** Strong oxidizing agents, strong alkalines, strong mineral acids.

**Conditions to avoid:** high heat, sparks, flames, static discharge.

**Hazardous Decomposition:** Oxidation may produce carbon and nitrogen oxides.  
Hazardous polymerization will not occur.

**SECTION 11 - Toxicological Information**

**Mixture Toxicity**

Inhalation Toxicity LC50: 629mg/L

**Component Toxicity**

123-86-4            n-Butyl acetate  
Inhalation LC50: 390 ppm (Rat)

108-65-6            Propylene glycol monomethyl ether acetate  
Dermal LD50: 5 g/kg (Rabbit)

**Primary Routes of Entry:** Inhalation, Skin Contact, Eyes, Ingestion

**Skin:**

Skin contact can cause redness, dryness or rash. Prolonged contact can cause irritation, dry skin, cracks, and dermatitis.

**Ingestion:**

Can cause vomiting, nausea, diarrhea, and gastrointestinal irritation.

**Inhalation:**

Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache possible unconsciousness and even asphyxiation. High vapor concentrations or prolonged breathing of lower concentrations may result in damage to the liver, kidneys, lungs and blood forming organs. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

**Eyes:**

Can cause irritation, redness, tearing and blurred vision.

**Carcinogenicity:** The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
None			N/A

**SECTION 12 - Ecological Information**

**Ecological Information:**

Uncontrolled release of the product may result in contamination of air, ground, waterways and/or sewers.

**Component Ecotoxicity**

n-Butyl acetate

LC50 96 h *Lepomis macrochirus* 100 mg/L [static] (EPA); LC50 96 h *Pimephales promelas* 17 - 19 mg/L [flow-through] (EPA)  
EC50 72 h *Desmodesmus subspicatus* 674.7 mg/L (IUCLID)

Propylene glycol monomethyl ether acetate

LC50 96 h *Pimephales promelas* 161 mg/L [static] (IUCLID)  
EC50 48 h *Daphnia magna* >500 mg/L (IUCLID)**SECTION 13 - Disposal Considerations**

Do not flush to sewer, watershed or waterway. Dispose of product in accordance with applicable local, county, state and federal regulations. See Section 8 for information on exposure control and necessary personal protective equipment.

**SECTION 14 - Transportation Information**

Ship according to the Department of Transportation (DOT) 49 CFR regulations.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	PAINT RELATED MATERIAL	UN1263	II	3
<b>Freight Class: 55</b>				

**SECTION 15 - Regulatory Information****Hazardous Material Information System (HMIS)**

HEALTH	<input type="checkbox"/>	<b>2</b>	<b>HMIS &amp; NFPA Hazard Rating Legend</b> * = Chronic Health Hazard <b>0 = INSIGNIFICANT</b> <b>1 = SLIGHT</b> <b>2 = MODERATE</b> <b>3 = HIGH</b>
FLAMMABILITY	<input type="checkbox"/>	<b>3</b>	
PHYSICAL HAZARD	<input type="checkbox"/>	<b>0</b>	
PERSONAL PROTECTION	<input checked="" type="checkbox"/>		

**SECTION 16 - Disclaimer**

Date Prepared: 11/19/2021

Date revised: 2021-09-20

Reviewer Revision 1

THIS DOCUMENT SUPERSEDES ANY PROVISION CONTAINED IN THE FORMS, LETTERS, AND PAPERS OF YOUR COMPANY. THIS PRODUCT IS DESIGNED AND INTENDED FOR PROFESSIONAL APPLICATION ONLY. ALL PRODUCTS SHOULD BE THOROUGHLY TESTED UNDER APPLICATION CONDITIONS PRIOR TO USE. THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE RELIABLE. HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED. INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OR WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER.