

PRODUCT: 6VDT073
DESCRIPTION: Clear Solvent Borne Binder
USE: Solvent Borne Binder for stains.
APPLICATION SYSTEM: Spray and wipe

CHEMICAL - PHYSICAL CHARACTERISTICS

SPECIFIC GRAVITY: 0.957 ± 0.010 (g/cc a 68° F)
DENSITY (WPG): 7.99 ± 0.010 (lbs/gal US at 68° F)
WEIGHT SOLIDS: 35% ± 1
VOLUME SOLIDS: 31.35% ± 1
VOC (material): 5.19 lbs/gal US or 622.05 g/l
VOC (coating): 5.19 lbs/gal US or 622.05 g/l
VOC Ratio: 1.86 lbs VOC/lbs Solids
HAPS Ratio: 0.54 lbs HAPS/lbs solids

PREPARATION OF THE PRODUCT

6VDT073 10 to 30% of this binder can be added to 6CTE5000US and / or 6CII stain concentrates along with reducers depending on the desired effect.

This product meets U.S.A. TSCA regulations.

GENERAL PROPERTIES

6VDT073 is a clear binder for solvent - borne stains for spray and wipe applications. It can be used with 6CTE and/or 6CII stain series. When using with solvent borne stains this binder will help to give your project a uniform effect while also highlighting the grain.

SHELF LIFE: 12 months.
Data refers to products preserved in original, sealed containers.

STORAGE: Keep in a fresh and well ventilated place; do not exceed 77°-82.4° F.

Company Information: SIRCA S.p.A. has a quality system certified by DNV GL ISO 9001



The information supplied are correct to the best of our knowledge. However, as the coating process depends on many variables and the present application takes place without our supervision, we cannot assume any responsibility for the final result. Sirca guarantees that chemical and physical characteristics of the products are within the reported range. Due to the large variety of substrates and application devices, the purchaser/user should test our products in his own application conditions and safety and environment circumstances. Sirca's technical and sales departments are at customer's disposal for any further information regarding correct application of our products.