



## Safety Data Sheet White WB EXT Sealer

Safety Data Sheet dated 3/25/2022, version 1

### 1. Identification

GHS Product identifier  
Mixture identification:  
Trade name: White WB EXT Sealer  
Other means of identification  
Trade code: 7FWP530  
Recommended use and restrictions on use  
Recommended use: Surface coating  
Uses advised against:  
---  
Supplier's details  
Company:  
SIRCA S.p.A.  
Viale Roma, 85  
35010 S. Dono di Massanzago (PD) - ITALY  
Tel. +39 0499322311  
Competent person responsible for the safety data sheet:  
safety@sirca.it  
Emergency phone number  
For Hazardous Materials [or Dangerous Goods] Incident  
Spill, Leak, Fire, Exposure, or Accident  
Call CHEMTREC Day or Night  
1-800-424-9300 / +1 703-527-3887.

### 2. Hazard identification

Classification of the hazardous product  
 Warning, Carc. 2, Suspected of causing cancer.

GHS label elements, including precautionary statements  
Hazard pictograms:



Warning  
Hazard statements:  
H351 Suspected of causing cancer.  
Precautionary statements:  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with applicable regulations.  
Special provisions  
None  
Other hazards  
None  
Ingredient(s) with unknown acute toxicity  
None.

### 3. Composition/Information on ingredients

Substances  
N.A.  
Mixtures  
Hazardous components within the meaning of WHMIS 2015 and related classification:  
>= 7% - < 9.9% Titanium dioxide  
REACH No.: 01-2119489379-17-xxxx, CAS: 13463-67-7, EC: 236-675-5  
 A.6/2 Carc. 2 H351  
  
>= 1% - < 2% 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether



## Safety Data Sheet

### White WB EXT Sealer

REACH No.: 01-2119475104-44-xxxx, Index number: 603-096-00-8, CAS: 112-34-5, EC: 203-961-6  
B.6/4 Flam. Liq. 4 H227



A.3/2A Eye Irrit. 2A H319

---

#### 4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

---

#### 5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO<sub>2</sub>).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:

N.A.

Oxidizing properties:

N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Wash with plenty of water.

---

#### 7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:



## Safety Data Sheet

### White WB EXT Sealer

Adequately ventilated premises.  
Storage temperature:  
Store at ambient temperature.

#### 8. Exposure controls/personal protection

##### Control parameters

Titanium dioxide - CAS: 13463-67-7  
ACGIH - TWA(8h): 10 mg/m<sup>3</sup> - Notes: A4 - LRT irr  
2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5  
(OEL (IT)) - TWA(8h): 67.5 mg/m<sup>3</sup>, 10 ppm - STEL: 101.2 mg/m<sup>3</sup>, 15 ppm - Behaviour: Binding  
EU - TWA(8h): 67.5 mg/m<sup>3</sup>, 10 ppm - STEL: 101.2 mg/m<sup>3</sup>, 15 ppm  
ACGIH - TWA(8h): 10 ppm - Notes: (IFV) - Hematologic, liver and kidney eff

##### DNEL Exposure Limit Values

Titanium dioxide - CAS: 13463-67-7  
Worker Industry: 10 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects  
Worker Professional: 10 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects  
Consumer: 700 mg/kg/day - Exposure: Human Oral - Frequency: Long Term, systemic effects  
2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5  
Worker Industry: 67.5 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects  
Worker Industry: 67.5 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
Worker Industry: 83 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
Worker Industry: 101.2 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term (acute)  
Consumer: 40.5 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
Consumer: 60.7 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term (acute)  
Consumer: 40.5 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects  
Consumer: 50 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
Consumer: 5 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

##### PNEC Exposure Limit Values

Titanium dioxide - CAS: 13463-67-7  
Target: Fresh Water - Value: 0.184 mg/l  
Target: Marine water - Value: 0.0184 mg/l  
Target: Soil (agricultural) - Value: 100 mg/kg  
Target: Marine water sediments - Value: 100 mg/kg - Notes:: dry  
Target: Freshwater sediments - Value: 1000 mg/kg - Notes:: dry  
Target: Soil (agricultural) - Value: 100 mg/kg - Notes:: alimento  
Target: orally (secondary poisoning) - Value: 1667 mg/kg  
2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5  
Target: Fresh Water - Value: 1 mg/l  
Target: Marine water - Value: 0.1 mg/l  
Target: occasional emission - Value: 3.9 mg/l  
Target: STP - Value: 200 mg/l  
Target: Freshwater sediments - Value: 4 mg/kg dwt  
Target: Marine water sediments - Value: 0.4 mg/kg dwt  
Target: Soil (agricultural) - Value: 0.4 mg/kg dwt  
Target: orally (secondary poisoning) - Value: 56 mg/kg

##### Appropriate engineering controls

None

Individual protection measures, such as personal protective equipment (PPE)

##### Eye protection:

Use close fitting safety goggles, don't use eye lens.

##### Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

##### Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

##### Respiratory protection:

Not needed for normal use.

##### Thermal Hazards:

None

#### 9. Physical and chemical properties

Appearance and colour:	liquid
Odour:	characteristic
Odour threshold:	N.A.
pH:	8.00
Melting point / freezing point:	< 1° C
Initial boiling point and boiling range:	> 55° C
Flash point:	N.A.
Evaporation rate:	N.A.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour pressure:	N.A.
Vapour density:	N.A.



## Safety Data Sheet

### White WB EXT Sealer

Relative density:	1.2200 Kg/l a 20°C
Solubility in water:	N.A.
Solubility in oil:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Auto-ignition temperature:	> 250° C
Decomposition temperature:	N.A.
Viscosity:	N.A.

#### 10. Stability and reactivity

Reactivity	Stable under normal conditions
Chemical stability	Stable under normal conditions
Possibility of hazardous reactions	No dangerous reaction is stored and used appropriately.
Conditions to avoid	Stable under normal conditions.
Incompatible materials	None in particular.
Hazardous decomposition products	None.

#### 11. Toxicological information

Information on toxicological effects	
Toxicological information of the product:	N.A.
Toxicological information of the main substances found in the product:	
Titanium dioxide - CAS: 13463-67-7	
a) acute toxicity:	Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg Test: LC50 - Route: Inhalation - Species: Rat > 6.82 mg/l - Duration: 4h Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg
b) skin corrosion/irritation:	Test: Eye Irritant - Species: Rabbit No Test: Skin Irritant - Species: Rabbit No
d) respiratory or skin sensitisation:	Test: Skin Sensitization - Species: Mouse No
i) STOT-repeated exposure:	Test: NOAEL - Species: Rat 3500 mg/kg/day - Source: polmoni
2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5	
a) acute toxicity:	Test: LC50 - Route: Inhalation - Species: Rabbit = 3 mg/l - Duration: 2h Test: LD50 - Route: Oral - Species: Rat = 5660 mg/kg Test: LD50 - Route: Skin - Species: Rabbit = 2700 mg/kg Test: LD50 - Route: Oral - Species: Mouse = 2400 mg/kg
Substance(s) listed on the NTP report on Carcinogens:	None.
Substance(s) listed on the IARC Monographs:	Titanium dioxide - Group 2B.
Substance(s) listed as OSHA Carcinogen(s):	None.
Substance(s) listed as NIOSH Carcinogen(s):	None.

#### 12. Ecological information

Ecotoxicity	Adopt good working practices, so that the product is not released into the environment.
Titanium dioxide - CAS: 13463-67-7	
a) Aquatic acute toxicity:	Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 Endpoint: EC50 - Species: Algae = 61 mg/l - Duration h: 72 Endpoint: EC50 - Species: Daphnia > 1000 mg/l - Duration h: 48
b) Aquatic chronic toxicity:	Endpoint: NOEC - Species: Algae 100000 mg/kg - Duration h: 480
2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5	
a) Aquatic acute toxicity:	Endpoint: LC50 - Species: Fish = 1300 mg/l - Duration h: 96 Endpoint: EC50 - Species: Daphnia = 100 mg/l - Duration h: 48
Persistence and degradability	N.A.
Bioaccumulative potential	



## Safety Data Sheet

### White WB EXT Sealer

N.A.  
Mobility in soil  
N.A.  
Other adverse effects  
None

---

#### 13. Disposal considerations

Safe handling and methods for disposal  
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

---

#### 14. Transport information

UN number  
UN number  
Not classified as dangerous in the meaning of transport regulations.  
UN proper shipping name  
N.A.  
Transport hazard class(es)  
N.A.  
Packing group  
N.A.  
Environmental hazards  
N.A.  
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)  
No  
Special precautions in connection with transport or conveyance  
N.A.

---

#### 15. Regulatory information

Safety, health and environmental regulations specific for the product in question  
This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) - WHMIS 2015.  
NPRI - National Pollutant Release Inventory  
Substance(s) listed under NPRI:  
None.  
DSL inventory - Domestic substances list  
All the components are listed in the DSL.  
NDSL inventory - Not Domestic substances list  
List of Components included in the NDSL (Not Domestic substances list)  
no substances listed  
TSCA inventory  
All the components are listed on the TSCA inventory.  
TSCA listed substances:  
None.  
USA - Federal regulations  
SARA - Superfund Amendments and Reauthorization Act  
Section 302 – Extremely Hazardous Substances: no substances listed.  
Section 304 – Hazardous substances: no substances listed.  
Section 313 – Toxic chemical list: no substances listed.  
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act  
No substances listed.  
CAA - Clean Air Act  
CAA listed substances:  
2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether is listed in CAA Section 111, Section 112(b) - HON.  
CWA - Clean Water Act  
CWA listed substances:  
None.  
USA - State specific regulations  
California Proposition 65  
Substance(s) listed under California Proposition 65:  
Titanium Dioxide (airborne, unbound particles of respirable size) is known to the state of California to cause cancer. This listing does not cover titanium dioxide when it remains bound within a product matrix  
None.  
Massachusetts Right to know  
Substance(s) listed under Massachusetts Right to know:  
Titanium dioxide.  
New Jersey Right to know  
Substance(s) listed under New Jersey Right to know:  
Titanium dioxide.  
Pennsylvania Right to know  
Substance(s) listed under Pennsylvania Right to know:



## Safety Data Sheet

### White WB EXT Sealer

Titanium dioxide.

#### 16. Other information

Text of phrases referred to under heading 3:  
H351 Suspected of causing cancer.  
H227 Combustible liquid.  
H319 Causes serious eye irritation.

Safety Data Sheet dated 3/25/2022, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average