



Safety Data Sheet Clear PU High gloss topcoat

Safety Data Sheet dated 4/28/2022, version 1







1. Identification

GHS Product identifier
Mixture identification:
Trade name: Clear PU High gloss topcoat
Other means of identification
Trade code: 7LPU136
Recommended use and restrictions on use
Recommended use: Surface coating
Uses advised against:

Supplier's details
Company:
SIRCA S.p.A.
Viale Roma, 85
35010 S. Dono di Massanzago (PD) - ITALY
Tel. +39 0499322311
Competent person responsible for the safety data sheet:
safety@sirca.it
Emergency phone number
For Hazardous Materials [or Dangerous Goods] Incident
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night
1-800-424-9300 / +1 703-527-3887.

2. Hazard identification

Classification of the hazardous product

-  Warning, Flam. Liq. 3, Flammable liquid and vapour.
-  Warning, Skin Irrit. 2, Causes skin irritation.
-  Warning, Eye Irrit. 2A, Causes serious eye irritation.
-  Warning, Carc. 2, Suspected of causing cancer.
-  Warning, STOT SE 3, May cause respiratory irritation.
-  Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

GHS label elements, including precautionary statements

Hazard pictograms:



Warning
Hazard statements:
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.
P242 Use non-sparking tools.

Safety Data Sheet

Clear PU High gloss topcoat

P243 Take action to prevent static discharges.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 Wash your face, hands and every exposed part thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water and soap.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P312 Call a POISON CENTER/ doctor/if you feel unwell.
 P314 Get medical advice/attention if you feel unwell.
 P321 Specific treatment (see supplementary instructions on this label).
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P370+P378.C In case of fire: Use a CO₂, Foam, Chemical powders for extinction.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with applicable regulations.

Special provisions

None

Other hazards

None

Ingredient(s) with unknown acute toxicity

None.

3. Composition/Information on ingredients

Substances

N.A.

Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

>= 25% - < 48% xylene [isomer mixture]

REACH No.: 01-2119488216-32-xxxx, Index number: 601-022-00-9, CAS: 1330-20-7, EC: 215-535-7



B.6/3 Flam. Liq. 3 H226



A.10/1 Asp. Tox. 1 H304



A.3/2A Eye Irrit. 2A H319



A.8/3 STOT SE 3 H335



A.9/2 STOT RE 2 H373



A.2/2 Skin Irrit. 2 H315



A.1/4/Dermal Acute Tox. 4 H312



A.1/4/Inhal Acute Tox. 4 H332

>= 7% - < 9.9% ethylbenzene

Index number: 601-023-00-4, CAS: 100-41-4, EC: 202-849-4



B.6/2 Flam. Liq. 2 H225



A.1/4/Inhal Acute Tox. 4 H332



A.2/2 Skin Irrit. 2 H315



Safety Data Sheet

Clear PU High gloss topcoat



A.6/2 Carc. 2 H351



A.10/1 Asp. Tox. 1 H304

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.
Remove contaminated clothing immediately and dispose off safely.
After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

In case of fire: Use a CO₂, Foam, Chemical powders for extinction.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.
Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:

N.A.

Oxidizing properties:

N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.
Remove all sources of ignition.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.
Provide adequate ventilation.
Use appropriate respiratory protection.
See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Wash with plenty of water.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Exercise the greatest care when handling or opening the container.
Do not use on extensive surface areas in premises where there are occupants.
Use localized ventilation system.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
See also section 8 for recommended protective equipment.
Advice on general occupational hygiene:
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities



Safety Data Sheet

Clear PU High gloss topcoat

Always keep in a well ventilated place.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from flame and sparks. Avoid accumulating electrostatic charge.
Place recipients on the ground whilst decanting, and wear anti-static clothing and shoes.

Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.
Safety electric system.
Storage temperature:
Store at ambient temperature.

8. Exposure controls/personal protection

Control parameters

xylene [isomer mixture] - CAS: 1330-20-7
(OEL (IT)) - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Behaviour: Binding - Notes: pelle
EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin
ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

ethylbenzene - CAS: 100-41-4
(OEL (IT)) - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Behaviour: Binding - Notes: pelle
EU - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Notes: Skin
ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair

DNEL Exposure Limit Values

xylene [isomer mixture] - CAS: 1330-20-7
Worker Industry: 180 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Industry: 77 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Consumer: 108 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Consumer: 1872 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
Consumer: 12.5 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

ethylbenzene - CAS: 100-41-4
Worker Industry: 180 mg/kg/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Industry: 293 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
Worker Industry: 77 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

xylene [isomer mixture] - CAS: 1330-20-7
Target: Fresh Water - Value: 0.327 mg/l
Target: Fresh Water - Value: 0.327 mg/l
Target: occasional emission - Value: 0.327 mg/l
Target: Microorganisms in sewage treatments - Value: 6.58 mg/l
Target: Soil (agricultural) - Value: 2.31 mg/kg - Notes: dry
Target: Marine water sediments - Value: 12.46 mg/kg - Notes: dry
Target: Freshwater sediments - Value: 12.46 mg/kg - Notes: dry

ethylbenzene - CAS: 100-41-4
Target: Fresh Water - Value: 0.1 mg/l
Target: Marine water - Value: 0.01 mg/l
Target: Freshwater sediments - Value: 13.7 mg/l
Target: Marine water sediments - Value: 13.7 mg/l
Target: occasional emission - Value: 0.1 mg/l

Appropriate engineering controls

None

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Use adequate protective respiratory equipment.

Thermal Hazards:

None

9. Physical and chemical properties

Appearance and colour:	liquid
Odour:	characteristic
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	< 1° C
Initial boiling point and boiling range:	> 55° C



Safety Data Sheet

Clear PU High gloss topcoat

Flash point:	N.A.
Evaporation rate:	N.A.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour pressure:	N.A.
Vapour density:	N.A.
Relative density:	0.9900 Kg/l a 20°C
Solubility in water:	N.A.
Solubility in oil:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Auto-ignition temperature:	> 250° C
Decomposition temperature:	N.A.
Viscosity:	N.A.

10. Stability and reactivity

Reactivity	It may generate dangerous reactions (See subsections below)
Chemical stability	It may generate dangerous reactions (See subsections below)
Possibility of hazardous reactions	No dangerous reaction is stored and used appropriately.
Conditions to avoid	Avoid accumulating electrostatic charge. Vapours can form explosive mixtures with air.
Incompatible materials	Avoid contact with combustible materials. The product could catch fire.
Hazardous decomposition products	None.

11. Toxicological information

Information on toxicological effects	Toxicological information of the product: N.A.
Toxicological information of the main substances found in the product:	xylene [isomer mixture] - CAS: 1330-20-7 a) acute toxicity: Test: LD50 - Route: Inhalation - Species: Rat = 27 mg/l - Duration: 4h Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg Test: LD50 - Route: Skin - Species: Rabbit = 12126 mg/kg ethylbenzene - CAS: 100-41-4 a) acute toxicity: Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg Test: LD50 - Route: Oral - Species: Rat = 4710 mg/kg body weight Test: LD50 - Route: Skin - Species: Rabbit = 15400 mg/kg Test: LCLo - Route: Inhalation - Species: Rat = 4000 Ppm - Duration: 4h d) respiratory or skin sensitisation: Test: Skin Sensitization - Route: Skin - Species: Cavia porcellus Negative
Substance(s) listed on the NTP report on Carcinogens:	None.
Substance(s) listed on the IARC Monographs:	xylene [isomer mixture] - Group 3 ethylbenzene - Group 2B.
Substance(s) listed as OSHA Carcinogen(s):	None.
Substance(s) listed as NIOSH Carcinogen(s):	None.

12. Ecological information

Ecotoxicity	Adopt good working practices, so that the product is not released into the environment. xylene [isomer mixture] - CAS: 1330-20-7 a) Aquatic acute toxicity: Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 48 Endpoint: LC50 - Species: Fish = 3.2 mg/l - Duration h: 96 Endpoint: LC50 - Species: Algae = 2.6 mg/l - Duration h: 73 ethylbenzene - CAS: 100-41-4 a) Aquatic acute toxicity: Endpoint: LC50 - Species: Fish = 42.3 mg/l - Duration h: 96
Persistence and degradability	N.A.
Bioaccumulative potential	



Safety Data Sheet

Clear PU High gloss topcoat

N.A.
Mobility in soil
N.A.
Other adverse effects
None

13. Disposal considerations

Safe handling and methods for disposal
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. Transport information

UN number
ADR-UN Number: 1263
DOT-UN Number: 1263
IATA-UN Number: 1263
IMDG-UN Number: 1263
UN proper shipping name
ADR-Shipping Name: Paint Related material
DOT-Shipping Name: Paint Related material
IATA-Shipping Name: Paint Related material
IMDG-Shipping Name: Paint Related material
Transport hazard class(es)
ADR-Class: 3
DOT-Class: 3
IATA-Class: 3
IMDG-Class: 3
Packing group
ADR-Packing Group: II
DOT-Packing Group: II
IATA-Packing group: II
IMDG-Packing group: II
Environmental hazards
ADR-Environmental Pollutant: No
IMDG-Marine pollutant: No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)
No
Special precautions
ADR-Tunnel Restriction Code: D/E
DOT-Special provisions: 149, B52, IB2, T4, TP1, TP8, TP28
IATA-Passenger Aircraft: 353
IATA-Cargo Aircraft: 364
IATA-S.P.: A72
IATA-ERG: 8L
IMDG-EmS: F-E, S-E
IMDG-Storage category: B
IMDG-Storage notes: None

15. Regulatory information

Safety, health and environmental regulations specific for the product in question
This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) - WHMIS 2015.
NPRI - National Pollutant Release Inventory
Substance(s) listed under NPRI:
None.
DSL inventory - Domestic substances list
All the components are listed in the DSL.
NDSL inventory - Not Domestic substances list
List of Components included in the NDSL (Not Domestic substances list)
no substances listed
TSCA inventory
List of substances included in the TSCA inventory:
xylene [isomer mixture]
List of substances not included in the TSCA inventory:
ethylbenzene
TSCA listed substances:
ethylbenzene is listed in TSCA Section 4.
USA - Federal regulations
SARA - Superfund Amendments and Reauthorization Act
Section 302 – Extremely Hazardous Substances: no substances listed.
Section 304 – Hazardous substances: no substances listed.



Safety Data Sheet

Clear PU High gloss topcoat

Section 313 – Toxic chemical list: xylene [isomer mixture], ethylbenzene.
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
Substance(s) listed under CERCLA: xylene [isomer mixture] - Reportable quantity: 100 pounds
ethylbenzene - Reportable quantity: 1000 pounds.
Reportable quantity for mixture: 246.381275 pounds.

CAA - Clean Air Act
CAA listed substances:
xylene [isomer mixture] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON
ethylbenzene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

CWA - Clean Water Act
CWA listed substances:
xylene [isomer mixture] is listed in CWA Section 311, Section 304
ethylbenzene is listed in CWA Section 311, Section 304, Section 307.

USA - State specific regulations
California Proposition 65
Substance(s) listed under California Proposition 65:
ethylbenzene - Listed as carcinogen.

Massachusetts Right to know
Substance(s) listed under Massachusetts Right to know:
xylene [isomer mixture]
ethylbenzene.

New Jersey Right to know
Substance(s) listed under New Jersey Right to know:
xylene [isomer mixture]
ethylbenzene.

Pennsylvania Right to know
Substance(s) listed under Pennsylvania Right to know:
xylene [isomer mixture]
ethylbenzene.

16. Other information

Text of phrases referred to under heading 3:
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H315 Causes skin irritation.
H312 Harmful in contact with skin.
H332 Harmful if inhaled.
H225 Highly flammable liquid and vapour.
H351 Suspected of causing cancer.

Safety Data Sheet dated 4/28/2022, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program



Safety Data Sheet

Clear PU High gloss topcoat

OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average