



TECHNICAL DATA SHEET

SBSS-8000
10 - 2022

PRODUCT : **SBSS-8000**
DESCRIPTION: Solvent Borne Spray Stain Base
USE: For Interior Wood Projects
APPLICATION SYSTEM: Spray and Wipe or Wipe

CHEMICAL - PHYSICAL CHARACTERISTICS

VISCOSITY: 14 #2 Zahn
WEIGHT SOLIDS: 0.83%
VOLUME SOLIDS: 0.69%
WEIGHT / GALLON: 7.22 lbs / gal
COVERAGE: 10.99 sq. ft. per gallon at one dry mil
VOC (material): 2.38 lbs/gal or 800 g/l
VOC (coating): 6.88 lbs/gal or 800 g/l
VOC Ratio: 39.85 lbs VOC/lbs solids
HAPS Ratio: 0.0 lbs HAPS/lbs solids

PREPARATION OF THE PRODUCT

SBSS-8000 100 Parts by weight
Colorants* 0 to 10 Parts by weight

*Colorant: This wiping stain base can be tinted with 6FBU's, 6CTE's and /or 6CII's

DRY TIMES: 1 hours before coating

GENERAL PROPERTIES

This Spray Stain Base has been developed to be tinted with 6FBU's, 6CTE's and / or 6CII's without the need to add additional solvents or reducers. This base is designed to be applied to sanded raw substrate. This base **can not** be used as a shade stain between clear coats, nor can it be added into a sealer or topcoat. Maximum tint load for this product is 10% by weight.

This Spray Stain Base was designed for industrial shops with excellent spray stain characteristics. SBSS-8000 has excellent color stability and settling properties. This product is short filled for tinting. Due to the colorants used to tint this base it is not recommended to be coated with any coatings that use an acid catalyst like PC's and CV's.

For additional information contact your local technical representative.

SHELF LIFE: 2 years

STORAGE: Keep in a cool, well ventilated place; temperature should not exceed 77°- 82.4° F.

The following supersedes any provision contained in the forms, letters and papers of your company. This product is designed and intended for professional application only. All products should be thoroughly tested under application conditions prior to use. The information contained herein is believed to be reliable. HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OF WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER. CAUTION: DANGER! FLAMMABLE! VAPORS MAY CAUSE FLASH FIRE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INJURIOUS TO EYES. KEEP OUT OF THE REACH OF CHILDREN! BEFORE using this product, it is essential that the "Material Safety Data Sheet" describing the product as well as the "Product Label" be reviewed. If your company does not have such information or has any questions, contact the manufacturer.