



Safety Data Sheet

Tobacco walnut Semitransp. Stain

Safety Data Sheet dated 4/15/2020, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name:

Tobacco walnut Semitransp. Stain

Other means of identification:

Trade code:

6CII971

Recommended use of the chemical and restrictions on use

Recommended use: Surface coating

Restrictions on use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

Sirca S.p.A.

Address:

Viale Roma, 85

35010 S. Dono di Massanzago (PD) - ITALY

Tel. +39 0499322311

Distributed by:

GEMINI INDUSTRIES, INC.

2300 Holloway Drive

El Reno, OK 73036

USA

Tel. 1-800-262-5710

Fax 1-405-262-9310

www.gemini-coatings.com

Competent person responsible for the safety data sheet:

safety@sirca.it

Emergency phone number

For Hazardous Materials [or Dangerous Goods] Incident

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

1-800-424-9300 / +1 703-527-3887.

2. HAZARD(S) IDENTIFICATION

Classification of the chemical



Danger, Flam. Liq. 2, Highly flammable liquid and vapour.



Warning, Skin Irrit. 2, Causes skin irritation.



Warning, Eye Irrit. 2A, Causes serious eye irritation.



Warning, Carc. 2, Suspected of causing cancer.



Warning, Repr. 2, Suspected of damaging fertility or the unborn child.



Warning, STOT SE 3, May cause drowsiness or dizziness.



Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.



Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways.

Label elements

Hazard pictograms:

6CII971/1

Page n. 1 of 12



Safety Data Sheet

Tobacco walnut Semitransp. Stain



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.

Precautionary statements:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash your face, hands and every exposed part thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
P302+P352 IF ON SKIN: Wash with plenty of water and soap.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER/doctor/... if you feel unwell.
P314 Get medical advice/attention if you feel unwell.
P321 Specific treatment (see supplementary instructions on this label).
P331 Do NOT induce vomiting.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire: Use a CO2, Foam, Chemical powders for extinction.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information

NFPA rating:





Safety Data Sheet

Tobacco walnut Semitransp. Stain

HMIS rating:

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL HAZARD		1
PERSONAL PROTECTION		

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 25% - < 48% toluene

REACH No.: 01-2119471310-51-xxxx, Index number: 601-021-00-3, CAS: 108-88-3, EC: 203-625-9



B.6/2 Flam. Liq. 2 H225



A.7/2 Repr. 2 H361



A.10/1 Asp. Tox. 1 H304



A.9/2 STOT RE 2 H373



A.2/2 Skin Irrit. 2 H315



A.8/3 STOT SE 3 H336

>= 12.5% - < 20% 1-methoxy-2-propanol

REACH No.: 01-2119457435-35-xxxx, Index number: 603-064-00-3, CAS: 107-98-2, EC: 203-539-1



B.6/3 Flam. Liq. 3 H226



A.8/3 STOT SE 3 H336

>= 12.5% - < 20% 2-ETHOXY-1-METHYLETHYL ACETATE

REACH No.: 01-2119475116-39-xxxx, Index number: 603-177-00-8, CAS: 54839-24-6, EC: 259-370-9



B.6/3 Flam. Liq. 3 H226



A.8/3 STOT SE 3 H336

>= 7% - < 9.9% xylene [isomer mixture]

REACH No.: 01-2119488216-32-xxxx, Index number: 601-022-00-9, CAS: 1330-20-7, EC: 215-535-7



B.6/3 Flam. Liq. 3 H226



A.10/1 Asp. Tox. 1 H304



Safety Data Sheet

Tobacco walnut Semitransp. Stain



A.3/2A Eye Irrit. 2A H319



A.8/3 STOT SE 3 H335



A.9/2 STOT RE 2 H373



A.2/2 Skin Irrit. 2 H315



A.1/4/Dermal Acute Tox. 4 H312



A.1/4/Inhal Acute Tox. 4 H332

>= 3% - < 5% acetone

REACH No.: 01-2119471330-49-xxxx, Index number: 606-001-00-8, CAS: 67-64-1, EC: 200-662-2



B.6/2 Flam. Liq. 2 H225



A.3/2A Eye Irrit. 2A H319



A.8/3 STOT SE 3 H336

>= 2.5% - < 3% 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve

REACH No.: 01-2119475108-36-xxxx, Index number: 603-014-00-0, CAS: 111-76-2, EC: 203-905-0



A.3/2A Eye Irrit. 2A H319



A.2/2 Skin Irrit. 2 H315



A.1/4/Oral Acute Tox. 4 H302



A.1/4/Dermal Acute Tox. 4 H312



A.1/4/Inhal Acute Tox. 4 H332

>= 1% - < 2% ethylbenzene

Index number: 601-023-00-4, CAS: 100-41-4, EC: 202-849-4



A.10/1 Asp. Tox. 1 H304



B.6/2 Flam. Liq. 2 H225



A.2/2 Skin Irrit. 2 H315



A.1/4/Inhal Acute Tox. 4 H332



A.6/2 Carc. 2 H351

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.



Safety Data Sheet

Tobacco walnut Semitransp. Stain

- Remove contaminated clothing immediately and dispose off safely.
- After contact with skin, wash immediately with soap and plenty of water.
- In case of eyes contact:
 - After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
 - Protect uninjured eye.
- In case of Ingestion:
 - Do NOT induce vomiting.
- In case of Inhalation:
 - Remove casualty to fresh air and keep warm and at rest.
- Most important symptoms/effects, acute and delayed
 - None
- Indication of immediate medical attention and special treatment needed
 - In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
- Treatment:
 - None

5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media:
 - In case of fire: Use a CO₂, Foam, Chemical powders for extinction.
- Unsuitable extinguishing media:
 - None in particular.
- Specific hazards arising from the chemical
 - Do not inhale explosion and combustion gases.
 - Burning produces heavy smoke.
- Hazardous combustion products:
 - None
- Explosive properties: N.A.
- Oxidizing properties: N.A.
- Special protective equipment and precautions for fire-fighters
 - Use suitable breathing apparatus .
 - Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
 - Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment, and emergency procedures
 - Wear personal protection equipment.
 - Remove all sources of ignition.
 - Remove persons to safety.
 - See protective measures under point 7 and 8.
- Methods and materials for containment and cleaning up
 - Wash with plenty of water.

7. HANDLING AND STORAGE

- Precautions for safe handling
 - Avoid contact with skin and eyes, inhalation of vapours and mists.
 - Exercise the greatest care when handling or opening the container.
 - Do not use on extensive surface areas in premises where there are occupants.
 - Don't use empty container before they have been cleaned.
 - Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
 - See also section 8 for recommended protective equipment.
 - Advice on general occupational hygiene:
 - Contaminated clothing should be changed before entering eating areas.
 - Do not eat or drink while working.
- Conditions for safe storage, including any incompatibilities
 - Always keep in a well ventilated place.
 - Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
 - Keep away from flame and sparks. Avoid accumulating electrostatic charge.
 - Place recipients on the ground whilst decanting, and wear anti-static clothing and shoes.
 - Keep away from food, drink and feed.
 - Incompatible materials:
 - None in particular.
 - Instructions as regards storage premises:
 - Cool and adequately ventilated.
 - Safety electric system.
 - Storage temperature:
 - Store at ambient temperature.



Safety Data Sheet

Tobacco walnut Semitransp. Stain

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

toluene - CAS: 108-88-3

(OEL (IT)) - TWA(8h): 192 mg/m3, 50 ppm - Behaviour: Binding - Notes: Pelle

EU - TWA(8h): 192 mg/m3, 50 ppm - STEL: 384 mg/m3, 100 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - Visual impair, female repro, pregnancy loss

1-methoxy-2-propanol - CAS: 107-98-2

(OEL (IT)) - TWA: 375 mg/m3, 100 ppm - STEL: 558 mg/m3, 150 ppm - Notes: pelle

NIOSH - TWA: 360 mg/m3, 100 ppm - STEL: 540 mg/m3, 150 ppm - Notes: 15 minutes average value

EU - TWA(8h): 375 mg/m3, 100 ppm - STEL: 563 mg/m3, 150 ppm - Notes: Skin

ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: A4 - Eye and URT irr

xylene [isomer mixture] - CAS: 1330-20-7

(OEL (IT)) - TWA(8h): 221 mg/m3, 50 ppm - STEL: 442 mg/m3, 100 ppm - Behaviour: Binding - Notes: pelle

EU - TWA(8h): 221 mg/m3, 50 ppm - STEL: 442 mg/m3, 100 ppm - Notes: Skin

ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

acetone - CAS: 67-64-1

Québec - TWA(8h): 1210 mg/m3, 500 ppm - Behaviour: Binding

TWA (Italia) - TWA: 1781 mg/m3

EU - TWA(8h): 1210 mg/m3, 500 ppm

ACGIH - TWA(8h): 250 ppm - STEL: 500 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

(OEL (IT)) - TWA(8h): 98 mg/m3, 20 ppm - STEL: 246 mg/m3, 50 ppm - Behaviour: Binding - Notes: pelle

EU - TWA(8h): 98 mg/m3, 20 ppm - STEL: 246 mg/m3, 50 ppm - Notes: Skin

MAK - TWA: 49 mg/m3, 10 ppm

ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - Eye and URT irr

ethylbenzene - CAS: 100-41-4

(OEL (IT)) - TWA(8h): 442 mg/m3, 100 ppm - STEL: 884 mg/m3, 200 ppm - Behaviour: Binding - Notes: pelle

EU - TWA(8h): 442 mg/m3, 100 ppm - STEL: 884 mg/m3, 200 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair

DNEL Exposure Limit Values

toluene - CAS: 108-88-3

Consumer: 226 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Consumer: 226 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, local effects

Consumer: 226 mg/m3 - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 56.5 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 8.13 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Industry: 384 mg/kg/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 384 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 192 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

1-methoxy-2-propanol - CAS: 107-98-2

Worker Industry: 553.5 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 50.6 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 369 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 18.1 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 43.9 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 3.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

2-ETHOXY-1-METHYLETHYL ACETATE - CAS: 54839-24-6

Worker Industry: 608 mg/m3 - Consumer: 365 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 103 mg/Kg-bw/day - Consumer: 62 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 302 mg/m3 - Consumer: 181 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 13.1 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

xylene [isomer mixture] - CAS: 1330-20-7

Worker Industry: 180 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 77 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 108 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 1872 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 12.5 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

acetone - CAS: 67-64-1

Worker Professional: 186 mg/kg/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Professional: 2420 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term (acute)

Worker Professional: 1210 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

Worker Industry: 89 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Worker Industry: 1091 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 246 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 125 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 98 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Exposure: Human Oral - Frequency: Short Term, systemic effects



Safety Data Sheet

Tobacco walnut Semitransp. Stain

Exposure: Human Oral - Frequency: Long Term, systemic effects
Consumer: 89 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects
Consumer: 426 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
Consumer: 147 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
Consumer: 75 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Consumer: 59 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Consumer: 26.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects
Consumer: 6.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

ethylbenzene - CAS: 100-41-4
Worker Industry: 180 mg/kg/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Industry: 293 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
Worker Industry: 77 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

toluene - CAS: 108-88-3
Target: Fresh Water - Value: 0.68 mg/l
Target: Marine water - Value: 0.68 mg/l
Target: Soil (agricultural) - Value: 2.89 mg/kg
Target: Marine water sediments - Value: 16.39 mg/l
Target: Freshwater sediments - Value: 16.39 mg/l
Target: STP - Value: 13.61 mg/l

1-methoxy-2-propanol - CAS: 107-98-2
Target: Fresh Water - Value: 10 mg/l
Target: Marine water - Value: 1 mg/l
Target: occasional emission - Value: 100 mg/l
Target: STP - Value: 100 mg/l
Target: Freshwater sediments - Value: 41.6 mg/kg
Target: Marine water sediments - Value: 4.17 mg/kg
Target: Soil (agricultural) - Value: 2.47 mg/kg

2-ETHOXY-1-METHYLETHYL ACETATE - CAS: 54839-24-6
Target: Fresh Water - Value: 1.3 mg/l
Target: Marine water - Value: 0.13 mg/l
Target: Freshwater sediments - Value: 6.4 mg/kg
Target: Marine water sediments - Value: 0.64 mg/kg
Target: Soil (agricultural) - Value: 1.34 mg/kg
Target: STP - Value: 62.5 mg/kg

xylene [isomer mixture] - CAS: 1330-20-7
Target: Fresh Water - Value: 0.327 mg/l
Target: Fresh Water - Value: 0.327 mg/l
Target: occasional emission - Value: 0.327 mg/l
Target: Microorganisms in sewage treatments - Value: 6.58 mg/l
Target: Soil (agricultural) - Value: 2.31 mg/kg - Notes:: dry
Target: Marine water sediments - Value: 12.46 mg/kg - Notes:: dry
Target: Freshwater sediments - Value: 12.46 mg/kg - Notes:: dry

acetone - CAS: 67-64-1
Target: Marine water - Value: 1.06 mg/l
Target: Marine water sediments - Value: 3.04 mg/l
Target: Fresh Water - Value: 30.4 mg/l
Target: Soil (agricultural) - Value: 29.5 mg/kg
Target: Freshwater sediments - Value: 30.4 mg/kg

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2
Target: Fresh Water - Value: 8.8 mg/l
Target: Marine water - Value: 0.88 mg/l
Target: Microorganisms in sewage treatments - Value: 463 mg/l
Target: Freshwater sediments - Value: 34.6 mg/kg
Target: Marine water sediments - Value: 3.46 mg/kg
Target: Soil (agricultural) - Value: 2.33 mg/l
Target: STP - Value: 463 mg/l
Target: orally (secondary poisoning) - Value: 20 mg/kg

ethylbenzene - CAS: 100-41-4
Target: Fresh Water - Value: 0.1 mg/l
Target: Marine water - Value: 0.01 mg/l
Target: Freshwater sediments - Value: 13.7 mg/l
Target: Marine water sediments - Value: 13.7 mg/l
Target: occasional emission - Value: 0.1 mg/l

Appropriate engineering controls:
None

Individual protection measures
Eye protection:
Use close fitting safety goggles, don't use eye lens.

Protection for skin:
Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:



Safety Data Sheet

Tobacco walnut Semitransp. Stain

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:	liquid
Odour:	characteristic
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	< 1° C
Initial boiling point and boiling range:	> 55° C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	< 21°C - < 69.8 °F
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	0.9300 Kg/l a 20°C
Solubility in water:	N.A.
Solubility in oil:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Auto-ignition temperature:	> 250° C
Decomposition temperature:	N.A.
Viscosity (typical value):	15.00 " Din cup # 4
Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

10. STABILITY AND REACTIVITY

Reactivity
It may generate dangerous reactions (See subsections below)

Chemical stability
It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions
No dangerous reaction is stored and used appropriately.

Conditions to avoid
Avoid accumulating electrostatic charge.
Vapours can form explosive mixtures with air.

Incompatible materials
Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products
None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

toluene - CAS: 108-88-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 5000 mg/kg - Duration: 24h

Test: LD50 - Route: Skin - Species: Rabbit 12267 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 25.7 mg/l - Duration: 4h

1-methoxy-2-propanol - CAS: 107-98-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 4016 mg/kg

Test: LC0 - Route: Inhalation Vapour - Species: Rat > 7000 Ppm - Duration: 6h

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg

b) skin corrosion/irritation:

Test: Skin Irritant Negative

c) serious eye damage/irritation:

Test: Eye Irritant Negative

2-ETHOXY-1-METHYLETHYL ACETATE - CAS: 54839-24-6

a) acute toxicity:

Test: LD50 - Route: Skin - Species: Rabbit = 13.42 ml/kg - Notes: Similar OCSE 403

Test: LC50 - Route: Inhalation - Species: Rat > 6.99 mg/l - Duration: 4h - Notes: Read - across



Safety Data Sheet

Tobacco walnut Semitransp. Stain

xylene [isomer mixture] - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: Inhalation - Species: Rat = 27 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 12126 mg/kg

acetone - CAS: 67-64-1

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 5800 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 7800 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 50100 mg/m3 - Duration: 8h

b) skin corrosion/irritation:

Test: Eye Irritant Yes

Test: Skin Irritant - Route: Skin Yes - Notes: Il contatto ripetuto può causare dermatiti

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Cavia porcellus 1300 mg/kg

Test: LD50 - Route: Skin - Species: Cavia porcellus > 2000 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Cavia porcellus > 400 Ppm - Duration: 7h

Test: LD50 - Route: Skin - Species: Rat 220 mg/kg

b) skin corrosion/irritation:

Test: Skin Irritant - Species: Rabbit Yes - Notes: Provoca irritazione cutanea

Test: Eye Irritant - Species: Rabbit Yes - Notes: provoca grave irritazione oculare

ethylbenzene - CAS: 100-41-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg

Test: LD50 - Route: Oral - Species: Rat = 4710 mg/kg body weight

Test: LD50 - Route: Skin - Species: Rabbit = 15400 mg/kg

Test: LCLo - Route: Inhalation - Species: Rat = 4000 Ppm - Duration: 4h

d) respiratory or skin sensitisation:

Test: Skin Sensitization - Route: Skin - Species: Cavia porcellus Negative

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

toluene - Group 3

xylene [isomer mixture] - Group 3

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - Group 3

ethylbenzene - Group 2B.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

toluene - CAS: 108-88-3

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 5.5 ml/l - Duration h: 96

Endpoint: EC50 - Species: Algae > 134 ml/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: EC50 - Species: Daphnia = 3.78 mg/l - Duration h: 48

1-methoxy-2-propanol - CAS: 107-98-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 6800 mg/l - Duration h: 96

Endpoint: LC50 - Species: Daphnia > 23300 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 168 - Notes: - (7d)

f) Effects in sewage plants:

Endpoint: EC50 - Species: Active mud > 1000 mg/l - Duration h: 3

2-ETHOXY-1-METHYLETHYL ACETATE - CAS: 54839-24-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 140 mg/l - Duration h: 96 - Notes: OCSE 203

Endpoint: EC50 - Species: Daphnia = 110 mg/l - Duration h: 48 - Notes: OCSE 202

Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 72 - Notes: OCSE 201

Endpoint: NOEC - Species: Algae > 100 mg/l - Duration h: 72 - Notes: OCSE 201

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish = 47.5 mg/l - Duration h: 96 - Notes: OCSE 204

Endpoint: NOEC - Species: Daphnia > 100 mg/l - Duration h: 504 - Notes: OCSE 211

xylene [isomer mixture] - CAS: 1330-20-7

a) Aquatic acute toxicity:



Safety Data Sheet

Tobacco walnut Semitransp. Stain

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 48
Endpoint: LC50 - Species: Fish = 3.2 mg/l - Duration h: 96
Endpoint: LC50 - Species: Algae = 2.6 mg/l - Duration h: 73
acetone - CAS: 67-64-1
a) Aquatic acute toxicity:
Endpoint: EC50 - Species: Daphnia = 8800 mg/kg
b) Aquatic chronic toxicity:
Endpoint: EC50 - Species: Fish = 6070 mg/l - Duration h: 96
Endpoint: NOEC - Species: Fish 6070 mg/l - Duration h: 96
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2
a) Aquatic acute toxicity:
Endpoint: LC50 - Species: Fish = 1490 mg/l - Duration h: 96
Endpoint: EC50 - Species: Daphnia = 1000 mg/l - Duration h: 24
c) Bacteria toxicity:
Endpoint: EC50 - Species: Active mud > 700 mg/l - Duration h: 16
ethylbenzene - CAS: 100-41-4
a) Aquatic acute toxicity:
Endpoint: LC50 - Species: Fish = 42.3 mg/l - Duration h: 96
Persistence and degradability
N.A.
Bioaccumulative potential
N.A.
Mobility in soil
N.A.
Other adverse effects
None

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

UN number
ADR-UN Number: 1263
DOT-UN Number: 1263
IATA-UN Number: 1263
IMDG-UN Number: 1263
UN proper shipping name
ADR-Shipping Name: Paint Related material
DOT-Shipping Name: Paint Related material
IATA-Shipping Name: Paint Related material
IMDG-Shipping Name: Paint Related material
Transport hazard class(es)
ADR-Class: 3
DOT-Class: 3
IATA-Class: 3
IMDG-Class: 3
Packing group
ADR-Packing Group: II
DOT-Packing Group: II
IATA-Packing group: II
IMDG-Packing group: II
Environmental hazards
ADR-Environmental Pollutant: No
IMDG-Marine pollutant: No
Special precautions
ADR-Tunnel Restriction Code: D/E
DOT-Special provisions: 149, B52, IB2, T4, TP1, TP8, TP28
IATA-Passenger Aircraft: 353
IATA-Cargo Aircraft: 364
IATA-S.P.: A72
IATA-ERG: 8L
IMDG-EmS: F-E, S-E
IMDG-Storage category: B
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)
No

15. REGULATORY INFORMATION

USA - Federal regulations

6CII971/1

Page n. 10 of 12



Safety Data Sheet

Tobacco walnut Semitransp. Stain

- TSCA - Toxic Substances Control Act
List of substances included in the TSCA inventory: toluene, 1-methoxy-2-propanol, xylene [isomer mixture], acetone, 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.
List of substances not included in the TSCA inventory: 2-ETHOXY-1-METHYLETHYL ACETATE, ethylbenzene.
TSCA listed substances:
toluene is listed in TSCA Section 8a - CAIR
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve is listed in TSCA Section 4, Section 12b.
- SARA - Superfund Amendments and Reauthorization Act
Section 302 – Extremely Hazardous Substances: no substances listed.
Section 304 – Hazardous substances: no substances listed.
Section 313 – Toxic chemical list: toluene, xylene [isomer mixture].
- CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
Substance(s) listed under CERCLA: toluene - Reportable quantity: 1000 pounds
xylene [isomer mixture] - Reportable quantity: 100 pounds
acetone - Reportable quantity: 5000 pounds.
Reportable quantity for mixture: 1417.433735 pounds.
- CAA - Clean Air Act
CAA listed substances:
toluene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON
1-methoxy-2-propanol is listed in CAA Section 112(b) - HON
xylene [isomer mixture] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON
acetone is listed in CAA Section 111, Section 112(b) - HON.
- CWA - Clean Water Act
CWA listed substances:
toluene is listed in CWA Section 311, Section 304, Section 307
xylene [isomer mixture] is listed in CWA Section 311, Section 304
acetone is listed in CWA Section 304.
- USA - State specific regulations
California Proposition 65
Substance(s) listed under California Proposition 65:
toluene - Listed as reproductive toxicant.
- Massachusetts Right to know
Substance(s) listed under Massachusetts Right to know:
toluene
1-methoxy-2-propanol
xylene [isomer mixture]
acetone
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.
- New Jersey Right to know
Substance(s) listed under New Jersey Right to know:
toluene
1-methoxy-2-propanol
xylene [isomer mixture]
acetone
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.
- Pennsylvania Right to know
Substance(s) listed under Pennsylvania Right to know:
toluene
1-methoxy-2-propanol
xylene [isomer mixture]
acetone
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.

16. OTHER INFORMATION

- Text of phrases referred to under heading 3:
H225 Highly flammable liquid and vapour.
H361 Suspected of damaging fertility or the unborn child.
H304 May be fatal if swallowed and enters airways.
H373 May cause damage to organs through prolonged or repeated exposure.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H312 Harmful in contact with skin.
H332 Harmful if inhaled.
H302 Harmful if swallowed.
H351 Suspected of causing cancer.

Safety Data Sheet dated 4/15/2020, version 1



Safety Data Sheet

Tobacco walnut Semitransp. Stain

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average