



Safety Data Sheet Rosewood Stain

Safety Data Sheet dated 11/4/2021, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: Rosewood Stain

Other means of identification:

Trade code: 6CTE5964US

Recommended use of the chemical and restrictions on use

Recommended use: Surface coating

Restrictions on use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

Sirca S.p.A.

Address:

Viale Roma, 85
35010 S. Dono di Massanzago (PD) - ITALY
Tel. +39 0499322311

Distributed by:

GEMINI INDUSTRIES, INC.
2300 Holloway Drive
El Reno, OK 73036
USA
Tel. 1-800-262-5710
Fax 1-405-262-9310
www.gemini-coatings.com

Competent person responsible for the safety data sheet:

safety@sirca.it

Emergency phone number

For Hazardous Materials [or Dangerous Goods] Incident
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night
1-800-424-9300 / +1 703-527-3887.

2. HAZARD(S) IDENTIFICATION

Classification of the chemical



Warning, Flam. Liq. 3, Flammable liquid and vapour.



Warning, Eye Irrit. 2A, Causes serious eye irritation.



Warning, Skin Sens. 1, May cause an allergic skin reaction.



Danger, Repr. 1B, May damage fertility or the unborn child.



Warning, STOT SE 3, May cause drowsiness or dizziness.

Aquatic Acute 3, Harmful to aquatic life.

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Label elements

Hazard pictograms:





Safety Data Sheet

Rosewood Stain

Danger

Hazard statements:

- H226 Flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H360 May damage fertility or the unborn child.
- H336 May cause drowsiness or dizziness.
- H402 Harmful to aquatic life.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash your face, hands and every exposed part thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 IF ON SKIN: Wash with plenty of water and soap.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER/doctor/... if you feel unwell.
- P321 Specific treatment (see supplementary instructions on this label).
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use a CO₂, Foam, Chemical powders for extinction.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information

NFPA rating:



HMIS rating:

HEALTH	*	3
FLAMMABILITY		3
PHYSICAL HAZARD		1
PERSONAL PROTECTION		

Safety Data Sheet

Rosewood Stain

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 75% 1-methoxy-2-propanol

REACH No.: 01-2119457435-35-xxxx, Index number: 603-064-00-3, CAS: 107-98-2, EC: 203-539-1



B.6/3 Flam. Liq. 3 H226



A.8/3 STOT SE 3 H336

>= 7% - < 9.9% 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve

REACH No.: 01-2119475108-36-xxxx, Index number: 603-014-00-0, CAS: 111-76-2, EC: 203-905-0



A.3/2A Eye Irrit. 2A H319



A.2/2 Skin Irrit. 2 H315



A.1/4/Oral Acute Tox. 4 H302



A.1/4/Dermal Acute Tox. 4 H312



A.1/4/Inhal Acute Tox. 4 H332

>= 5% - < 7% Sodium 6-amino-5-[[2-[(ethylphenylamino)sulphonyl]phenyl]azo]-4-hydroxynaphthalene-2-sulphonate

REACH No.: 01-2120770130-68-xxxx, CAS: 70865-30-4, EC: 274-958-5



A.3/2A Eye Irrit. 2A H319

>= 2.5% - < 3% trisodium bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-)

REACH No.: 01-2119969289-17-xxxx, CAS: 57693-14-8, EC: 260-906-9



A.3/2A Eye Irrit. 2A H319



A.4.2/1 Skin Sens. 1 H317

US-HAE/C3 Aquatic Chronic 3 H412

>= 0.25% - < 0.5% Acid Yellow 220

REACH No.: 01-2120065791-52-xxxx, EC: 941-792-6



A.9/2 STOT RE 2 H373



US-HAE/A1 Aquatic Acute 1 H400



US-HAE/C1 Aquatic Chronic 1 H410



A.3/2A Eye Irrit. 2A H319



A.4.2/1 Skin Sens. 1 H317

>= 0.2% - < 0.25% 2-methoxypropanol

Index number: 603-106-00-0, CAS: 1589-47-5, EC: 216-455-5




Safety Data Sheet

Rosewood Stain

 B.6/3 Flam. Liq. 3 H226

 A.7/1B Repr. 1B H360

 A.8/3 STOT SE 3 H335


 A.2/2 Skin Irrit. 2 H315

 A.3/1 Eye Dam. 1 H318

>= 0.1% - < 0.2% C.I. Acid yellow 151

REACH No.: 01-2120071400-71-xxxx, CAS: 72496-88-9, EC: 276-701-2

US-HAE/C3 Aquatic Chronic 3 H412

 A.4.2/1 Skin Sens. 1 H317

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.
Remove contaminated clothing immediately and dispose off safely.
After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire: Use a CO₂, Foam, Chemical powders for extinction.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.
Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:

N.A.

Oxidizing properties:

N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.
Remove all sources of ignition.
Remove persons to safety.
See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.



Safety Data Sheet

Rosewood Stain

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Exercise the greatest care when handling or opening the container.
Do not use on extensive surface areas in premises where there are occupants.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
See also section 8 for recommended protective equipment.
Advice on general occupational hygiene:
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from flame and sparks. Avoid accumulating electrostatic charge.
Place recipients on the ground whilst decanting, and wear anti-static clothing and shoes.

Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.
Safety electric system.
Storage temperature:
Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

1-methoxy-2-propanol - CAS: 107-98-2
(OEL (IT)) - TWA: 375 mg/m³, 100 ppm - STEL: 558 mg/m³, 150 ppm - Notes: pelle
NIOSH - TWA: 360 mg/m³, 100 ppm - STEL: 540 mg/m³, 150 ppm - Notes: 15 minutes average value
EU - TWA(8h): 375 mg/m³, 100 ppm - STEL: 563 mg/m³, 150 ppm - Notes: Skin
ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: A4 - Eye and URT irr

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2
(OEL (IT)) - TWA(8h): 98 mg/m³, 20 ppm - STEL: 246 mg/m³, 50 ppm - Behaviour: Binding - Notes: pelle
EU - TWA(8h): 98 mg/m³, 20 ppm - STEL: 246 mg/m³, 50 ppm - Notes: Skin
MAK - TWA: 49 mg/m³, 10 ppm
ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - Eye and URT irr

2-methoxypropanol - CAS: 1589-47-5
TWA (Italia) - TWA: 375 mg/m³, 100 ppm
(STEL(IE)) - TWA: 568 mg/m³, 150 ppm

DNEL Exposure Limit Values

1-methoxy-2-propanol - CAS: 107-98-2
Worker Industry: 553.5 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
Worker Industry: 50.6 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Industry: 369 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Consumer: 18.1 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Consumer: 43.9 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Consumer: 3.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2
Worker Industry: 89 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects
Worker Industry: 1091 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
Worker Industry: 246 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
Worker Industry: 125 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Industry: 98 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Exposure: Human Oral - Frequency: Short Term, systemic effects
Exposure: Human Oral - Frequency: Long Term, systemic effects
Consumer: 89 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects
Consumer: 426 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
Consumer: 147 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
Consumer: 75 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Consumer: 59 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Consumer: 26.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects
Consumer: 6.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

trisodium bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-) - CAS: 57693-14-8
Worker Industry: 24.5 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Worker Industry: 27.78 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Consumer: 14.7 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Consumer: 16.7 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Consumer: 8.33 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects



Safety Data Sheet

Rosewood Stain

2-methoxypropanol - CAS: 1589-47-5

Worker Industry: 553.5 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 183 mg/kg - Consumer: 78 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 369 mg/m³ - Consumer: 43.9 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 33 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

1-methoxy-2-propanol - CAS: 107-98-2

Target: Fresh Water - Value: 10 mg/l

Target: Marine water - Value: 1 mg/l

Target: occasional emission - Value: 100 mg/l

Target: STP - Value: 100 mg/l

Target: Freshwater sediments - Value: 41.6 mg/kg

Target: Marine water sediments - Value: 4.17 mg/kg

Target: Soil (agricultural) - Value: 2.47 mg/kg

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

Target: Fresh Water - Value: 8.8 mg/l

Target: Marine water - Value: 0.88 mg/l

Target: Microorganisms in sewage treatments - Value: 463 mg/l

Target: Freshwater sediments - Value: 34.6 mg/kg

Target: Marine water sediments - Value: 3.46 mg/kg

Target: Soil (agricultural) - Value: 2.33 mg/l

Target: STP - Value: 463 mg/l

Target: orally (secondary poisoning) - Value: 20 mg/kg

trisodium bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-) - CAS: 57693-14-8

Target: orally (secondary poisoning) - Value: 33.3 mg/kg

Target: Soil (agricultural) - Value: 600 mg/kg

Target: Fresh Water - Value: 3 µg/L

Target: Marine water - Value: 0.3 µg/L

Target: Freshwater sediments - Value: 3000 mg/kg

Target: Marine water sediments - Value: 300 mg/kg

Target: STP - Value: 0.781 mg/l

2-methoxypropanol - CAS: 1589-47-5

Target: Fresh Water - Value: 10 mg/l

Target: Marine water - Value: 1 mg/l

Target: occasional emission - Value: 100 mg/l

Target: Microorganisms in sewage treatments - Value: 100 mg/l

Target: Freshwater sediments - Value: 41.6 mg/kg

Target: Soil (agricultural) - Value: 2.47 mg/kg

Target: Marine water sediments - Value: 4.17 mg/kg

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:	liquid
Odour:	characteristic
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	< 1° C
Initial boiling point and boiling range:	> 55° C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	21°C <= fp < 55°C (69.8°F <= fp < 131°F)
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	0.9500 Kg/l a 20°C
Solubility in water:	N.A.
Solubility in oil:	N.A.
Partition coefficient (n-octanol/water):	N.A.



Safety Data Sheet

Rosewood Stain

Auto-ignition temperature:	> 250° C
Decomposition temperature:	N.A.
Viscosity (typical value):	10.00 " Din cup # 4
Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

10. STABILITY AND REACTIVITY

Reactivity
It may generate dangerous reactions (See subsections below)

Chemical stability
It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions
No dangerous reaction is stored and used appropriately.

Conditions to avoid
Avoid accumulating electrostatic charge.
Vapours can form explosive mixtures with air.

Incompatible materials
Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products
None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects
Toxicological information of the product:
N.A.

Toxicological information of the main substances found in the product:

1-methoxy-2-propanol - CAS: 107-98-2

a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat = 4016 mg/kg
Test: LC0 - Route: Inhalation Vapour - Species: Rat > 7000 Ppm - Duration: 6h
Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg

b) skin corrosion/irritation:
Test: Skin Irritant Negative

c) serious eye damage/irritation:
Test: Eye Irritant Negative

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

a) acute toxicity:
Test: LD50 - Route: Oral - Species: Cavia porcellus 1300 mg/kg
Test: LD50 - Route: Skin - Species: Cavia porcellus > 2000 mg/kg
Test: LC50 - Route: Inhalation Vapour - Species: Cavia porcellus > 400 Ppm - Duration: 7h

b) skin corrosion/irritation:
Test: Skin Irritant - Species: Rabbit Yes - Notes: Provoca irritazione cutanea
Test: Eye Irritant - Species: Rabbit Yes - Notes: provoca grave irritazione oculare

trisodium bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-) - CAS: 57693-14-8

a) acute toxicity:
Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg body weight - Source: OECD402

Acid Yellow 220

a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat 3.934 mg/kg bw/day

b) skin corrosion/irritation:
Test: Skin Irritant - Species: Rabbit No
Test: Eye Irritant - Species: Rabbit Positive

d) respiratory or skin sensitisation:
Test: Skin Sensitization - Species: Cavia porcellus Yes

C.I. Acid yellow 151 - CAS: 72496-88-9

a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat > 10000 mg/kg bw/day

b) skin corrosion/irritation:
Test: Skin Irritant - Species: Cavia porcellus No

Substance(s) listed on the NTP report on Carcinogens:
None.

Substance(s) listed on the IARC Monographs:
2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - Group 3.

Substance(s) listed as OSHA Carcinogen(s):
None.



Safety Data Sheet

Rosewood Stain

Substance(s) listed as NIOSH Carcinogen(s):
None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

1-methoxy-2-propanol - CAS: 107-98-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 6800 mg/l - Duration h: 96

Endpoint: LC50 - Species: Daphnia > 23300 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 168 - Notes: - (7d)

f) Effects in sewage plants:

Endpoint: EC50 - Species: Active mud > 1000 mg/l - Duration h: 3

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve - CAS: 111-76-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 1490 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 1000 mg/l - Duration h: 24

c) Bacteria toxicity:

Endpoint: EC50 - Species: Active mud > 700 mg/l - Duration h: 16

trisodium bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-) - CAS: 57693-14-8

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 30.2 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 3 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae 73.8 mg/l - Duration h: 72

Acid Yellow 220

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia 30.5 mg/l - Duration h: 48

Endpoint: ErC50 - Species: Algae 96 mg/l - Duration h: 168

C.I. Acid yellow 151 - CAS: 72496-88-9

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae 31.8 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia 55 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish 42.5 mg/l - Duration h: 96

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

None

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

UN number

ADR-UN Number: 1263

DOT-UN Number: 1263

IATA-UN Number: 1263

IMDG-UN Number: 1263

UN proper shipping name

ADR-Shipping Name: Paint Related material

DOT-Shipping Name: Paint Related material

IATA-Shipping Name: Paint Related material

IMDG-Shipping Name: Paint Related material

Transport hazard class(es)

ADR-Class: 3

DOT-Class: 3

IATA-Class: 3

IMDG-Class: 3

Packing group

ADR-Packing Group: II

DOT-Packing Group: II

IATA-Packing group: II

IMDG-Packing group: II

Environmental hazards

ADR-Environmental Pollutant: No



Safety Data Sheet

Rosewood Stain

IMDG-Marine pollutant: No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)
No
Special precautions
ADR-Tunnel Restriction Code: D/E
DOT-Special provisions: 149, B52, IB2, T4, TP1, TP8, TP28
IATA-Passenger Aircraft: 353
IATA-Cargo Aircraft: 364
IATA-S.P.: A72
IATA-ERG: 8L
IMDG-EmS: F-E, S-E
IMDG-Storage category: B
IMDG-Storage notes: None

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

List of substances included in the TSCA inventory: 1-methoxy-2-propanol, 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve, Sodium 6-amino-5-[[2-[(ethylphenylamino)sulphonyl]phenyl]azo]-4-hydroxynaphthalene-2-sulphonate, trisodium bis[3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(3-), 2-methoxypropanol.

List of substances not included in the TSCA inventory: Acid Yellow 220, C.I. Acid yellow 151.

TSCA listed substances:

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve is listed in TSCA Section 4, Section 12b.

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: no substances listed.

Section 313 – Toxic chemical list: no substances listed.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

No substances listed.

CAA - Clean Air Act

CAA listed substances:

1-methoxy-2-propanol is listed in CAA Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

None.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

None.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

1-methoxy-2-propanol

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

1-methoxy-2-propanol

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

1-methoxy-2-propanol

2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve.

16. OTHER INFORMATION

Text of phrases referred to under heading 3:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H360 May damage fertility or the unborn child.

H335 May cause respiratory irritation.

H318 Causes serious eye damage.



Safety Data Sheet

Rosewood Stain

Safety Data Sheet dated 11/4/2021, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average