



Safety Data Sheet Black WB 2K EXT INT Sealer

Safety Data Sheet dated 1/25/2021, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: Black WB 2K EXT INT Sealer

Other means of identification:

6FWBP440 Trade code:

Recommended use of the chemical and restrictions on use

Recommended use:Surface coating Restrictions on use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: Sirca S.p.A.

Address:

Viale Roma, 85

35010 S.Dono di Massanzago (PD) - ITALY

Tel. +39 0499322311

Distributed by:

GEMINI INDUSTRIES, INC.

2300 Holloway Drive El Reno, OK 73036

USA

Tel. 1-800-262-5710

Fax 1-405-262-9310

www.gemini-coatings.com

Competent person responsible for the safety data sheet:

safety@sirca.it

Emergency phone number

For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night

1-800-424-9300 / +1 703-527-3887.

2. HAZARD(S) IDENTIFICATION

Classification of the chemical



Warning, Carc. 2, Suspected of causing cancer.



Danger, STOT RE 1, Causes damage to organs through prolonged or repeated exposure.

Label elements Hazard pictograms:



Danger

Hazard statements:

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash with water thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention. P314 Get medical advice/attention if you feel unwell.

P405 Store locked up.
P501 Dispose of contents/container in accordance with applicable regulations.



Black WB 2K EXT INT Sealer

Special Provisions:

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.
Additional classification information

NFPA rating:



HMIS rating:



3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 3% -< 5% Talc

CAS: 14807-96-6, EC: 238-877-9



A.9/1 STOT RE 1 H372

>= 2% - < 2.5% 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether REACH No.: 01-2119475104-44-xxxx, Index number: 603-096-00-8, CAS: 112-34-5, EC: 203-961-6



4.3/2A Eye Irrit. 2A H319

>= 0.5% - < 1% C.I. Carbon black 7

REACH No.: 01-2119384822-32-xxxx, CAS: 1333-86-4, EC: 215-609-9



A.6/2 Carc. 2 H351

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

6FWBP440/1



Black WB 2K EXT INT Sealer

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases. Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.
Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities
Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature:

Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Talc - CAS: 14807-96-6

ACGIH - TWA(8h): 2 mg/m3 - Notes: Containing no asbestos fibers. (E,R), A4 - Pulm fibrosis, pulm func

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

(OEL (IT)) - TWA(8h): 67.5 mg/m3, 10 ppm - STEL: 101.2 mg/m3, 15 ppm - Behaviour: Binding EU - TWA(8h): 67.5 mg/m3, 10 ppm - STEL: 101.2 mg/m3, 15 ppm ACGIH - TWA(8h): 10 ppm - Notes: (IFV) - Hematologic, liver and kidney eff C.I. Carbon black 7 - CAS: 1333-86-4 ACGIH - TWA(8h): 3 mg/m3 - Notes: (I), A3 - Bronchitis

Ontario - TWA(8h): 3.5 mg/m3

DNEL Exposure Limit Values

. 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

Worker Industry: 67.5 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, local effects Worker Industry: 67.5 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects



Black WB 2K EXT INT Sealer

Worker Industry: 83 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects Worker Industry: 101.2 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term (acute) Consumer: 40.5 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects Consumer: 60.7 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term (acute)

Consumer: 40.5 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, local effects
Consumer: 50 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Consumer: 5 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects
C.I. Carbon black 7 - CAS: 1333-86-4

Worker Industry: 2 mg/m3 - Exposure: Human Inhalation - Notes: (frazione inspirabile)

PNEC Exposure Limit Values

 $\dot{2}$ -(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

Target: Fresh Water - Value: 1 mg/l Target: Marine water - Value: 0.1 mg/l Target: occasional emission - Value: 3.9 mg/l Target: STP - Value: 200 mg/l

Target: Freshwater sediments - Value: 4 mg/kg dwt Target: Marine water sediments - Value: 0.4 mg/kg dwt Target: Soil (agricultural) - Value: 0.4 mg/kg dwt

Target: orally (secondary poisoning) - Value: 56 mg/kg

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour: liquid Odour: characteristic Odour threshold: N.A pH: Melting point / freezing point: Initial boiling point and boiling range: 8.00 < 1° C > 55° C

Solid/gas flammability: N.A. Upper/lower flammability or explosive limits: Vapour density:

Flash point: other >=55°C (>=131°F)

Evaporation rate: N.A. N.A

Vapour pressure: Relative density: 1.2100 Kg/l a 20°C

Solubility in water: N.A. Solubility in oil: N.A. Partition coefficient (n-octanol/water): N.A. Auto-ignition temperature: > 250° C N.A

Decomposition temperature: 30.00 " Din cup #6 Viscosity (typical value):

Miscibility: N.A. Fat Solubility: N.A. N.A. Substance Groups relevant properties

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

No dangerous reaction is stored and used appropriately.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.



Safety Data Sheet Black WB 2K EXT INT Sealer

Hazardous decomposition products None.

```
11. TOXICOLOGICAL INFORMATION
          Information on toxicological effects
          Toxicological information of the product:
          Toxicological information of the main substances found in the product:
                    Talc - CAS: 14807-96-6
a) acute toxicity:
                               Test: LD50 - Route: Oral > 5000 mg/kg body weight
                    b) skin corrosion/irritation:
                               Test: Skin Irritant No
                     2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5
                     a) acute toxicity:
                               Test: LC50 - Route: Inhalation - Species: Rabbit = 3 mg/l - Duration: 2h
                               Test: LD50 - Route: Oral - Species: Rat = 5660 mg/kg
Test: LD50 - Route: Oral - Species: Rat = 5660 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit = 2700 mg/kg
                               Test: LD50 - Route: Oral - Species: Mouse = 2400 mg/kg
                     C.I. Carbon black 7 - CAS: 1333-86-4
                     a) acute toxicity:
                               Test: LD50 - Route: Oral - Species: Rat > 8000 mg/kg
                    b) skin corrosion/irritation:
                               Test: Skin Irritant - Species: Rabbit No
                    Test: Eye Irritant - Species: Rabbit No
d) respiratory or skin sensitisation:
                               Test: Skin Sensitization - Species: Cavia porcellus No
          Substance(s) listed on the NTP report on Carcinogens:
                    None.
          Substance(s) listed on the IARC Monographs:
```

None. 12. ECOLOGICAL INFORMATION

None.

Talc - Group 3 C.I. Carbon black 7 - Group 2B. Substance(s) listed as OSHA Carcinogen(s):

Substance(s) listed as NIOSH Carcinogen(s):

```
Ecotoxicity
```

```
Adopt good working practices, so that the product is not released into the environment.
         2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5
         a) Aquatic acute toxicity:
                  Endpoint: LC50 - Species: Fish = 1300 mg/l - Duration h: 96
                  Endpoint: EC50 - Species: Daphnia = 100 mg/l - Duration h: 48
         C.I. Carbon black 7 - CAS: 1333-86-4
         a) Aquatic acute toxicity:
Endpoint: LC0 - Species: Fish 1000 mg/l - Duration h: 96
                  Endpoint: LC0 - Species: Fish 5000 mg/l - Duration h: 14
                  Endpoint: EC0 - Species: Daphnia 5600 mg/l - Duration h: 24
                  Endpoint: CE10 - Species: Active mud > 800 mg/l - Duration h: 3
         b) Aquatic chronic toxicity:
                  Endpoint: NOEC - Species: Algae 10000 mg/l - Duration h: 72
Persistence and degradability
Bioaccumulative potential
         N.A.
Mobility in soil
         N.A.
Other adverse effects
         None
```

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

6FWBP440/1



Black WB 2K EXT INT Sealer

UN proper shipping name

Transport hazard class(es)

N.A.

Packing group

NΑ

Environmental hazards N.A.

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

Special precautions

N.A.

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act
TSCA inventory: all the components are listed on the TSCA inventory.
TSCA listed substances:

None.

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances: no substances listed.

Section 304 - Hazardous substances: no substances listed. Section 313 - Toxic chemical list: no substances listed.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

No substances listed. CAA - Clean Air Act

CAA listed substances:

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether is listed in CAA Section 111, Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

C.I. Carbon black 7 - Listed as carcinogen.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

C.I. Carbon black 7.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

Talc

C.I. Carbon black 7.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Talc C.I. Carbon black 7.

16. OTHER INFORMATION

Text of phrases referred to under heading 3:

H372 Causes damage to organs through prolonged or repeated exposure. H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

Safety Data Sheet dated 1/25/2021, version 1

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures) CAS:

Chemical Abstracts Service (division of the American Chemical Society). Classification, Labeling, Packaging.

CLP:

DNEL: Derived No Effect Level.

European Inventory of Existing Commercial Chemical Substances.
Globally Harmonized System of Classification and Labeling of Chemicals. EINECS:

HMIS: Hazardous Materials Identification System IARC: International Agency for Research on Cancer



Black WB 2K EXT INT Sealer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

International Civil Aviation Organization.
Technical Instructions by the "International Civil Aviation Organization" (ICAO).

ICAO: ICAO-TI: IMDG: INCI: KSt: International Maritime Code for Dangerous Goods. International Nomenclature of Cosmetic Ingredients. Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

NFPA: National Fire Protection Association NIOSH:

NTP: OSHA: PNEC: RID:

National Fire Protection Association
National Institute for Occupational Safety and Health
National Toxicology Program
Occupational Safety and Health Administration
Predicted No Effect Concentration.
Regulation Concerning the International Transport of Dangerous Goods by Rail.
Short Term Exposure limit.

STEL: STOT: Specific Target Organ Toxicity. TLV: Threshold Limiting Value. TWA: Time-weighted average