





# **Safety Data Sheet** White WB 2K INT EXT Matt topcoat

#### Safety Data Sheet dated 12/15/2022, version 1

#### 1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name:

White WB 2K INT EXT Matt topcoat

Other means of identification: Trade code:

6OWBP043G20

Recommended use of the chemical and restrictions on use

Recommended use:Surface coating

Restrictions on use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: Sirca S.p.A.

Address:

Viale Roma, 85

35010 S.Dono di Massanzago (PD) - ITALY Tel. +39 0499322311

Distributed by:

GEMINI INDUSTRIES, INC.

2300 Holloway Drive

El Reno, OK 73036

USA

Tel. 1-800-262-5710

Fax 1-405-262-9310

www.gemini-coatings.com

Competent person responsible for the safety data sheet:

safety@sirca.it

Emergency phone number

For Hazardous Materials [or Dangerous Goods] Incident

Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night 1-800-424-9300 / +1 703-527-3887.

# 2. HAZARD(S) IDENTIFICATION Classification of the chemical



Warning, Skin Sens. 1, May cause an allergic skin reaction.



Warning, Carc. 2, Suspected of causing cancer.

Aquatic Acute 3, Harmful to aquatic life.

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

# Label elements

Hazard pictograms:





Warning

Hazard statements:

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects. Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.



# White WB 2K INT EXT Matt topcoat P302+P352 IF ON SKIN: Wash with plenty of water and soap. P308+P313 IF exposed or concerned: Get medical advice/attention. P321 Specific treatment (see supplementary instructions on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information

NFPA rating:



HMIS rating:



# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 9.9% - < 12.5% Titanium dioxide
REACH No.: 01-2119489379-17-xxxx, CAS: 13463-67-7, EC: 236-675-5



A.6/2 Carc. 2 H351

>= 2% - < 2.5% 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether REACH No.: 01-2119475104-44-xxxx, Index number: 603-096-00-8, CAS: 112-34-5, EC: 203-961-6



A.3/2A Eye Irrit. 2A H319

>= 0.25% - < 0.5% Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. REACH No.: 01-2119491304-40-xxxx, EC: 915-687-0



4.4.2/1 Skin Sens. 1 H317



US-HAE/A1 Aquatic Acute 1 H400



US-HAE/C1 Aquatic Chronic 1 H410

#### 4. FIRST-AID MEASURES

6OWBP043G20/1



## White WB 2K INT EXT Matt topcoat

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest. Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

# **5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).
Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:
Oxidizing properties:

N.A. N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

## **6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove persons to safety. See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

#### 7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed. Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature:

Store at ambient temperature.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Titanium dioxide - CAS: 13463-67-7

ACGIH - TWA(8h): 10 mg/m3 - Notes: A4 - LRT irr

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

(OEL (IT)) - TWA(8h): 67.5 mg/m3, 10 ppm - STEL: 101.2 mg/m3, 15 ppm - Behaviour: Binding EU - TWA(8h): 67.5 mg/m3, 10 ppm - STEL: 101.2 mg/m3, 15 ppm

ACGIH - TWA(8h): 10 ppm - Notes: (IFV) - Hematologic, liver and kidney eff



# White WB 2K INT EXT Matt topcoat

```
DNEL Exposure Limit Values
```

Titanium dioxide - CAS: 13463-67-7

Worker Industry: 10 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, local effects Worker Professional: 10 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, local effects Consumer: 700 mg/kg/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

Worker Industry: 67.5 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, local effects Worker Industry: 67.5 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 83 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects Worker Industry: 101.2 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term (acute) Consumer: 40.5 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects Consumer: 60.7 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term (acute) Consumer: 40.5 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 50 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects Consumer: 5 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate.

Worker Industry: 1.27 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 1.8 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects Consumer: 0.9 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects Consumer: 0.31 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects Consumer: 0.18 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

Titanium dioxide - CAS: 13463-67-7
Target: Fresh Water - Value: 0.184 mg/l
Target: Marine water - Value: 0.0184 mg/l
Target: Soil (agricultural) - Value: 100 mg/kg - Notes:: dry
Target: Marine water sediments - Value: 100 mg/kg - Notes:: dry

Target: Freshwater sediments - Value: 1000 mg/kg - Notes:: dry Target: Soil (agricultural) - Value: 100 mg/kg - Notes:: alimento Target: orally (secondary poisoning) - Value: 1667 mg/kg

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5
Target: Fresh Water - Value: 1 mg/l
Target: Marine water - Value: 0.1 mg/l
Target: occasional emission - Value: 3.9 mg/l

Target: STP - Value: 200 mg/l

Target: Freshwater sediments - Value: 4 mg/kg dwt Target: Marine water sediments - Value: 0.4 mg/kg dwt Target: Soil (agricultural) - Value: 0.4 mg/kg dwt

Target: orally (secondary poisoning) - Value: 56 mg/kg
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate.

Target: Fresh Water - Value: 0.0022 mg/l

Target: Marine water - Value: 0.00022 mg/l Target: occasional emission - Value: 0.009 mg/l Target: Freshwater sediments - Value: 1.05 mg/kg Target: Marine water sediments - Value: 0.11 mg/kg Target: Soil (agricultural) - Value: 0.21 mg/kg Target: STP - Value: 1 mg/l

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour: liquid Odour: characteristic Odour threshold: NΑ pH: Melting point / freezing point: 8 00 < 1° C Initial boiling point and boiling range: > 55° C Solid/gas flammability: N.A. Upper/lower flammability or explosive limits: N.A. Vapour density: N.A. Evaporation rate: N.A. Vapour pressure: NΑ



## White WB 2K INT EXT Matt topcoat

Relative density: Solubility in water: 1.1250 Kg/l a 20°C

N.A. Solubility in oil: N.A. Partition coefficient (n-octanol/water): N.A. Auto-ignition temperature: > 250° C Decomposition temperature: N.A.

35.00 " Viscosity (typical value): Din cup # 6

Miscibility: Fat Solubility: N A N.A. N.A. Conductivity: Substance Groups relevant properties N.A.

#### 10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

No dangerous reaction is stored and used appropriately.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

## 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

NΑ

Toxicological information of the main substances found in the product:

Titanium dioxide - CAS: 13463-67-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 6.82 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

b) skin corrosion/irritation:

Test: Eye Irritant - Species: Rabbit No Test: Skin Irritant - Species: Rabbit No

d) respiratory or skin sensitisation:

Test: Skin Sensitization - Species: Mouse No

i) STOT-repeated exposure: Test: NOAEL - Species: Rat 3500 mg/kg/day - Source: polmoni

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rabbit = 3 mg/l - Duration: 2h Test: LD50 - Route: Oral - Species: Rat = 5660 mg/kg Test: LD50 - Route: Skin - Species: Rabbit = 2700 mg/kg Test: LD50 - Route: Oral - Species: Mouse = 2400 mg/kg

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate.

a) acute toxicity: Test: LD50 - Route: Oral - Species: Rat > 3230 mg/kg

b) skin corrosion/irritation:

Test: Skin Irritant - Species: Rabbit Negative

c) serious eye damage/irritation:

Test: Eye Irritant - Species: Rabbit Negative

d) respiratory or skin sensitisation:

Test: Skin Sensitization - Species: Cavia porcellus Positive

Substance(s) listed on the NTP report on Carcinogens:

None

Substance(s) listed on the IARC Monographs:

Titanium dioxide - Group 2B.
Substance(s) listed as OSHA Carcinogen(s):

Substance(s) listed as NIOSH Carcinogen(s):

None

# 12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.



# White WB 2K INT EXT Matt topcoat

```
Titanium dioxide - CAS: 13463-67-7 a) Aquatic acute toxicity:
                      Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96
                      Endpoint: EC50 - Species: Algae = 61 mg/l - Duration h: 72
Endpoint: EC50 - Species: Daphnia > 1000 mg/l - Duration h: 48
           b) Aquatic chronic toxicity:
Endpoint: NOEC - Species: Algae 100000 mg/kg - Duration h: 480
           2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5
           a) Aquatic acute toxicity:
                      Endpoint: LC50 - Species: Fish = 1300 mg/l - Duration h: 96
Endpoint: EC50 - Species: Daphnia = 100 mg/l - Duration h: 48
           Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate.
           a) Aquatic acute toxicity:
                      Endpoint: LC50 - Species: Fish = 0.97 mg/l
Endpoint: EC50 - Species: Daphnia = 20 mg/l
                      Endpoint: EC50 - Species: Algae = 1.68 mg/l
           b) Aquatic chronic toxicity:
Endpoint: NOEC - Species: Daphnia = 1 mg/kg - Notes: (21d)
           f) Effects in sewage plants:
                      Endpoint: EC50 - Species: Active mud > 100 mg/l
Persistence and degradability
           N.A
Bioaccumulative potential
           N.A
Mobility in soil
           N.A.
Other adverse effects
           None
```

#### 13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force

## 14. TRANSPORT INFORMATION

UN number

Not classified as dangerous in the meaning of transport regulations.

UN proper shipping name

N.A

Transport hazard class(es)

N.A.

Packing group Ň.A.

Environmental hazards N A

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code) No

Special precautions

N.A.

#### 15. REGULATORY INFORMATION

```
USA - Federal regulations
```

TSCA - Toxic Substances Control Act

TSCA inventory: all the components are listed on the TSCA inventory.

TSCA listed substances:

None.

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: no substances listed.

Section 313 - Toxic chemical list: no substances listed. CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

No substances listed.

CAA - Clean Air Act

CAA listed substances:

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether is listed in CAA Section 111, Section 112(b) - HON. CWA - Clean Water Act

CWA listed substances:

None.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:



# White WB 2K INT EXT Matt topcoat

Titanium Dioxide (airborne, unbound particles of respirable size) is known to the state of California to cause cancer. This listing does not cover titanium dioxide when it remains bound within a product matrix

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

Titanium dioxide.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

Titanium dioxide.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Titanium dioxide.

#### **16. OTHER INFORMATION**

Text of phrases referred to under heading 3:

H351 Suspected of causing cancer.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Safety Data Sheet dated 12/15/2022, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

European Agreement concerning the International Carriage of Dangerous Goods by Road. ADR:

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

European Inventory of Existing Commercial Chemical Substances.
Globally Harmonized System of Classification and Labeling of Chemicals.
Hazardous Materials Identification System **EINECS:** GHS:

HMIS: IARC: International Agency for Research on Cancer IATA: International Air Transport Association.

Dangerous Goods Regulation by the "International Air Transport Association" (IATA). IATA-DGR:

ICAO: ICAO-TI: International Civil Aviation Organization.
Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods. International Nomenclature of Cosmetic Ingredients. INCI:

Explosion coefficient. KSt:

LC50: Lethal concentration, for 50 percent of test population. LD50: Lethal dose, for 50 percent of test population.

NFPA: National Fire Protection Association

National Institute for Occupational Safety and Health National Toxicology Program NIOSH: NTP: OSHA:

Occupational Safety and Health Administration Predicted No Effect Concentration. PNEC:

Regulation Concerning the International Transport of Dangerous Goods by Rail. RID:

Short Term Exposure limit. STEL: STOT: Specific Target Organ Toxicity. TLV: Threshold Limiting Value. TWA-Time-weighted average