



1. Identification

Product identifier	ACLEAR WIPING STAIN BASE
Product code	ÁÚÓÝ ÓË €€€Á
Other means of identification	N.Av.
Recommended use of the chemical and restrictions on use	PAINT.
Manufacturer	GEMINI INDUSTRIES, INC. 2300 Holloway Drive El Reno, OK 73036 USA Tel. 1-800-262-5710 Fax 1-405-262-9310 www.gemini-coatings.com
Emergency phone number	INFOTRAC 800-535-5053 Outside USA, Call Collect 1-352-323-3500 (French & English) 24-hour HAZMAT Response and MSDS help: EMI 800-510-8510

2. Hazard identification

Summary	DANGER! FLAMMABLE LIQUID! TOXIC! Harmful by inhalation or if absorbed through the skin. Harmful or fatal if inhaled into the lungs (ingestion/vomiting). May cause irritation to skin and eyes. May cause central nervous system effects. Contains a substance that can cause target organ damage, according to data obtained on animals. Contains a substance that can cause cancer based on animal data. Keep away from heat, sparks and open flame. Avoid contact with skin, eyes and clothing. Do not breathe vapours, mists or aerosols. Do not ingest. If ingested consult physician immediately and show this Safety Data Sheet. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet. Keep containers tightly closed when not in use. After use, wash hands with soap and water. Wash contaminated clothing before reuse.
----------------	--

WHMIS 2015/OSHA HCS 2012/GHS

	Flammable liquids (Category 3) Acute toxicity, inhalation (Category 4) Skin irritation (Category 2) Eye irritation (Category 2) Carcinogenicity (Category 2) Specific target organ toxicity, single exposure, Narcotic effects (Category 3) Aspiration hazard (Category 1)
	Other hazards which do not result in classification : Acute hazard to the aquatic environment (Category 1). Long-term hazard to the aquatic environment (Category 1).

DANGER

H226: Flammable liquid and vapour
 H304: May be fatal if swallowed and enters airways
 H332: Harmful if inhaled

H319: Causes serious eye irritation
H315: Causes skin irritation
H336: May cause drowsiness or dizziness
H351: Suspected of causing cancer
H410: Very toxic to aquatic life with long lasting effects
P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat, sparks, open flames and other ignition sources. No smoking.
P240: Ground or bond container and receiving equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P261: Avoid breathing vapours.
P264: Wash skin thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.
P280: Wear protective gloves, protective clothing and eye protection.
P301+310+331: IF SWALLOWED: Immediately call a POISON CENTER or a physician. Do NOT induce vomiting.
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water and soap or take a shower if necessary.
P332+313: If skin irritation occurs: Get medical advice or attention.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.
P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P337+313: If eye irritation persists: Get medical advice or attention.
P362+364: Take off contaminated clothing and wash before reuse.
P370+378: In case of fire: Use chemical foam, dry chemical or carbon dioxide to extinguish.
P391: Collect spillage.
P403+P235+P233: Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P501: Dispose of contents and container to an approved waste disposal plant.

3. Composition/information on ingredients

Common name	CAS	Weight % content
Solvent naphtha (petroleum), light aromatic (C8 to C10)	64742-95-6	30 - 60 %
Stoddard solvent (Mineral Spirits)	8052-41-3	15 - 40 %
Naphthalene	91-20-3	3 - 7 %
2-Butoxyethanol	111-76-2	3 - 7 %
1,2,4-Trimethylbenzene	95-63-6	1 - 5 %
Synthetic Amorphous Fumed Silica	112945-52-5	1 - 5 %

4. First-aid measures

Inhalation	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.
Skin contact	Wash skin with warm water and mild soap. Remove contaminated clothing and wash before reuse. Avoid touching eyes with contaminated body parts. If a problem develops or persists, seek medical attention.
Eye contact	IMMEDIATELY flush with plenty of water. Remove contact lenses. Flush with water for at least 15 minutes. Hold eyelids apart to rinse properly. If a problem develops or persists, seek medical attention.
Ingestion	DO NOT induce vomiting, unless recommended by medical personnel. Never give anything by mouth if victim is unconscious or convulsing. If spontaneous vomiting occurs, keep head below hip level to prevent aspiration into the lungs. Seek medical attention or contact a Poison Centre immediately.

Other	No information available.
Symptoms	Aspiration hazard for the lungs (ingestion/vomiting). Can enter lungs and cause damage. Signs of lung involvement include increased respiratory rate, increased heart rate, and a bluish discolouration of the skin. Coughing, choking and gagging are often noted at the time of aspiration.
Notes to the physician	Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media	dried powder, carbon dioxide (CO ₂), alcohol resistant foam, Do not use a heavy water jet.
Specific hazards arising from the chemical	NFPA: Class IC Flammable liquid. Vapours are heavier than air and may travel to an ignition source distant from the material handling point. May be ignited by heat, sparks, flame or static electricity. Do not apply to hot surfaces. Contact with strong oxidizers may cause fire. In a fire or if heated, a pressure increase will occur and the container may burst. Emits toxic fumes under fire conditions.
Special protective equipment	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.
Special protective actions for fire-fighters	Water stream can scatter and spread fire. If water is used, fog nozzles are preferable. Use water spray to cool fire-exposed containers.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.
Environmental precautions	Prevent entry in sewer and other enclosed area. For a large spill, consult the Department of Environment or the relevant authorities.
Methods and materials for containment and cleaning up	Remove sources of ignition. Ventilate the area well. Stay against the wind spill. Make sure you have a fire extinguisher near you. Stop leak, if it's possible to do so without risk. Use non-sparking and antistatic tools. Absorb with inert material (soil, sand, vermiculite) or wipe up or scrape up and place in an appropriate waste disposal container clearly identified. Dispose via a licensed waste disposal contractor. Finish cleaning the contaminated surface by rinsing with soapy water.

7. Handling and storage

Precautions for safe handling	Keep away from heat, sparks and open flame. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Use non-sparking and antistatic tools. Ground/bond all containers when transferring large quantities (5 gallons US or 20 L and more). Use only in well ventilated area. Avoid prolonged or repeated breathing of vapour or mists. Avoid contact with skin, eyes and clothing. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet. Keep containers tightly closed when not in use. Containers of this material may be hazardous even when empty. Since empty containers retain product residues (vapour, liquid), all hazard precautions given in this sheet must be observed. Do not eat, do not drink and do not smoke during use. Wash hands, forearms and face thoroughly after handling this compound and before eating, drinking or using toiletries. Remove contaminated clothing and wash before reuse.
Conditions for safe storage, including any incompatibilities	Storage and handling should follow the NFPA 30 Flammable and/or Combustible Liquids Code and the National Fire Code of Canada (NFCC). NFPA: Class IC Flammable liquid. Store tightly closed and in properly labelled container in a dry, cool and well ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from oxidizing materials and incompatible materials (see section 10).

Storage temperature	10 to 25°C (50 to 77°F)
----------------------------	-------------------------

8. Exposure controls/personal protection

Immediately Dangerous to Life or Health	Stoddard solvent (Mineral Spirits): 20000 mg/m ³ . Naphthalene: 250 ppm. 2-Butoxyethanol: 700 ppm. Synthetic Amorphous Fumed Silica: 3000 mg/m ³ .		
Stoddard solvent (Mineral Spirits)	STEL		580 mg/m ³ BC
	TWA (8h)		290 mg/m ³ BC
		100 ppm	525 mg/m ³ ACGIH , ON, RSST
		100 ppm	572 mg/m ³ AB
2-Butoxyethanol	TWA (8h)	20 ppm	ACGIH , BC, ON
		20 ppm	97 mg/m ³ AB , RSST
Naphthalene	STEL	15 ppm	BC
		15 ppm	78 mg/m ³ ON
		15 ppm	79 mg/m ³ AB , ACGIH, RSST
	TWA (8h)	10 ppm	BC
		10 ppm	52 mg/m ³ AB , ACGIH, ON, RSST
1,2,4-Trimethylbenzene	TWA (8h)	25 ppm	ACGIH , BC, ON
		25 ppm	123 mg/m ³ AB , RSST
Synthetic Amorphous Fumed Silica	TWA (8h)	Respirable Dust	1.5 mg/m ³ BC
		Respirable Dust	3 mg/m ³ ACGIH , ON
		Total Dust	4 mg/m ³ BC
		Respirable Dust	6 mg/m ³ RSST
		Total Dust	10 mg/m ³ ACGIH , ON
Appropriate engineering controls	Provide sufficient mechanical ventilation (general or local exhaust) to keep the airborne concentrations of vapours, mists, aerosols or dust below their respective occupational exposure limits.		
Individual protection measures			
Eye	Wear safety glasses. If there is a risk of contact with eyes, wear chemical splash goggles.		
Hands	In case of prolonged contact wear neoprene or nitrile gloves. Before using, user should confirm impermeability. Discard gloves with tears, pinholes, or signs of wear. Gloves must only be worn on clean hands. Wash gloves with water before removing them. After using gloves, hands should be washed and dried thoroughly. Disposable nitrile gloves can also be used, but discard after single use.		
Skin	Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear normal work clothing covering arms and legs as required by employer code. Wear synthetic apron, if necessary, to prevent repeated or prolonged contact with skin.		
Respiratory	Where the conditions in the workplace require a respirator, it is necessary to follow a respiratory protection program. Moreover, respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and standard 29 CFR 1910.134 (OSHA), ANSI Z88.2 or CSA Z 94.11 (Canada) and approved by NIOSH/MSHA. In case of insufficient ventilation or in enclosed area until maximum 10 times of exposure limit, wear half mask respirator with organic vapors cartridges and fitted with a particulate filter.		
Feet	Wear rubber boots to clean up a spill.		

9. Physical and chemical properties

Physical state	Liquid	Flammability	Flammable
Colour	Clear	Flammability limits	1.2 to 12%
Odour	Solvent odor	Flash point	37.8°C (100°F)
Odour threshold	N/Av.	Auto-ignition temperature	N/Av.
pH	N/Ap.	Sensibility to electrostatic charges	Yes
Melting point	N/Av.	Sensibility to sparks and/or friction	N/Av.
Freezing point	N/Av.	Vapour density	>1 (Air = 1)
Boiling point	N/Av.	Relative density	0.872 kg/L (Water = 1)
Solubility	No	Partition coefficient n-octanol/water	N/Av.
Evaporation rate	> Butyl Acetate	Decomposition temperature	N/Av.
Vapour pressure	N/Av.	Viscosity	N/Av.
Percent Volatile	94.24%	Molecular mass	N/Ap.
N/Av.: Not Available N/Ap.: Not Applicable Und.: Undetermined N/E: Not Established			

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions (including polymerizations)	A dangerous reaction will not occur.
Conditions to avoid	Avoid heat, flame and sparks. Avoid contact with incompatible materials.
Incompatible materials	Strong oxidants, strong bases, mineral acids, strong acids.
Hazardous decomposition products	In combustion: nitrogen oxides, carbon oxides (CO, CO ₂).

11. Toxicological information


Numerical measures of toxicity	Solvent naphtha (petroleum), light aromatic (C8 to C10)	Ingestion	8400 mg/kg	Rat	LD50
		Inhalation	>5.2 mg/l/4h	Rat	LC50
		Skin	>3750 mg/kg	Rabbit	LD50
	Stoddard solvent (Mineral Spirits)	Ingestion	>5000 mg/kg	Rat	LD50
		Inhalation	>12 mg/l/4h	Rat	LC50
		Skin	>3000 mg/kg	Rabbit	LD50
	2-Butoxyethanol	Ingestion	560 mg/kg	Rat	LD50
		Inhalation	2.21 mg/l/4h	Rat	LC50
		Skin	220 mg/kg	Rabbit	LD50
	Naphthalene	Ingestion	490 mg/kg	Rat	LD50
		Inhalation	>1 mg/l/1h	Rat	LC50

	1,2,4-Trimethylbenzene	Skin 1120 mg/kg Rabbit LD50 Ingestion 5000 mg/kg Rat LD50 Inhalation 18 mg/l/4h Rat LC50
	Synthetic Amorphous Fumed Silica	Skin >3160 mg/kg Rabbit LD50 Ingestion >5000 mg/kg Rat LD50 Inhalation >2.08 mg/l/4h Rat LC50 Skin >5000 mg/kg Rabbit LD50
Likely routes of exposure	Skin, eyes, inhalation, ingestion.	
Delayed, immediate and chronic effects	Eye contact	May cause eye irritation.
	Skin contact	May cause skin irritation. Prolonged and repeated contact may cause drying and cracking of the skin. Widespread contact with skin for several hours can cause harmful amounts of material to be absorbed.
	Inhalation	Excessive inhalation is harmful. May cause slight upper respiratory tract irritation. High concentrations may cause central nervous system depression characterized by headache, dizziness, nausea, fatigue, drowsiness, unconsciousness, asphyxia. The severity of symptoms may vary depending on exposure conditions. Prolonged and repeated exposure may cause damage to liver, kidneys, lungs and blood forming organs.
	Ingestion	May cause gastro-intestinal irritation with nausea and vomiting. Harmful or fatal if inhaled into the lungs (ingestion/vomiting). Contains a substance that can cause target organ damage, according to data obtained on animals.
	IARC/NTP Classification	Common name IARC NTP Naphthalene 2B R IARC : 1- Carcinogenic; 2A- Probably carcinogenic; 2B- Possibly carcinogenic. NTP : K- Known to be carcinogens; R- Reasonably anticipated to be carcinogens.
	Carcinogenicity	Contains a substance that can cause cancer based on animal data. The risk of cancer depends on duration and level of exposure.
	Teratogenicity	This material is not known to cause teratogenic effect.
	Mutagenicity	This material is not known to cause mutagenic effect.
	Reproductive toxicity	This material is not known to cause effects on reproduction.
	Immunotoxicity	No information available.
Interactive effects	No information available for this product.	
Other information	Target organs: central nervous system, kidneys, liver, lungs. blood forming organs. The acute toxicity estimate (ATE) by inhalation of the mixture was calculated to be greater than 10 mg/L/4h but lower than 20 mg/L/4h. This value is classified according to GHS: Acute toxicity, inhalation (Category 4). The oral and skin acute toxicity estimates (ATE) of the mixture were calculated to be greater than 2000 mg/kg. These values are not classified according to WHMIS 2015 and OSHA HCS 2012.	


12. Ecological information

Ecological toxicity	N/Av. LC50 N/Av.
Persistence	Contains an ingredient which is a marine pollutant.
Degradability	No information available for this product.
Bioaccumulative potential	No information available for this product.
Mobility in soil	No information available for this product.
Other adverse effects	Toxic to aquatic organisms, cause long-term adverse effects in the aquatic environment.

13. Disposal considerations

Container 	<p>Important! Prevent waste generation. Use in full. DO NOT dispose residue in sewers, streams or drinking water supply. Paint residues including lacquer, thinner, stain, shellac, varnish, polish can be reprocessed everywhere there is a recycling program. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.</p>
--	--

14. Transport information

UN Number	UN 1263
UN Proper Shipping Name	PAINT
Environmental hazards	Contains an ingredient which is a marine pollutant.
Special precautions for user	No information available.
TDG - Transportation of Dangerous Goods (Canada)	
Transport hazard class(es)	 Class 3
Packing group	III
IMO/IMDG - International Maritime Transport	
Classification	Regulated UN 1263. Class 3, PG III.
IATA - International Air Transport Association	
Classification	Regulated UN 1263. Class 3, PG III.
<p>These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. In addition, if a domestic exemption exists, it is the responsibility of the shipper to define the application of it.</p>	

15. Regulatory information

Other regulations	<p>UNITED STATE OF AMERICA:</p> <ul style="list-style-type: none"> - Toxic Substance Control Act (TSCA) : All ingredients are listed in the TSCA Inventory. - EPCRA Section 313 Toxic Chemicals: 1,2,4-Trimethylbenzene (CAS no. 95-63-6). Naphtalene (CAS no. 91-20-3). - California Proposition 65: Contains ingredients that can cause cancer according to the state of California. Naphtalene (CAS no. 91-20-3). <p>CANADA :</p> <ul style="list-style-type: none"> - Canada DSL and NDSL: All ingredients are listed in the Domestic Substances List (DSL). - Canadian National Pollutant Release Inventory Substances (NPRI): Stoddard solvent (Mineral Spirits) (CAS No. 8052-41-3). 1,2,4-Trimethylbenzene (CAS no. 95-63-6). Naphtalene (CAS no. 91-20-3). 2-Butoxyethanol (CAS no. 111-76-2). Solvent naphtha (petroleum), light aromatic (C8 to C10) (CAS no. 64742-95-6).
--------------------------	---

WHMIS 1988

B2 D1A D2A D2B

Class B2 : Flammable Liquid

Class D1A : Very toxic material causing immediate and serious toxic effects

Class D2A : Very toxic material causing other toxic effects

Class D2B : Toxic material causing other toxic effects

HMIS**NFPA****16. Other information**

Date
(YYYY-MM-DD)

GEMINI INDUSTRIES, INC. 2014-12-09

Version

02

Other information

DATE OF FIRST VERSION OF SDS:

2014-10-16

CHANGES MADE IN THE VERSION 02:

sections 5, 7 and 14.

REFERENCES:

- Haz-Map, Information on Hazardous Chemicals and Occupational Diseases,

<http://hazmap.nlm.nih.gov/index.php>

- Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST), <http://www.reptox.csst.qc.ca>

- NIOSH Pocket Guide to Chemical Hazards, Centers for Disease Control and Prevention, NIOSH Publications, 2007, <http://www.cdc.gov/niosh/npg/npg.html>

- IPCS INCHEM, Chemical Safety Information from Intergovernmental Organizations, Canadian Centre for Occupational Health and Safety (CCOHS), Copyright International Programme on Chemical Safety (IPCS), <http://www.inchem.org>

- IUCLID Chemical Dataset, European Chemical Substances Information System (ESIS), Joint Research Centre, <http://esis.jrc.ec.europa.eu>

- OECD Existing Chemicals Database, Chemicals Screening Information Data Set (SIDS) for High Volume Chemicals, UNEP publications, <http://webnet.oecd.org/HPV/UI/Search.aspx>

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

HMIS: Hazardous Materials Identification System

NFPA: National Fire Protection Association

OSHA: Occupational Safety and Health Administration (USA)

NIOSH: National Institute for Occupational Safety and Health

NTP: National Toxicology Program

RSST: Règlement sur la santé et la sécurité du travail (Québec)

GHS: Globally Harmonized System

IARC: International Agency for Research on Cancer

IDLH: Immediately Dangerous to Life or Health

STEL: Short Term Exposure Limit (15 min)

TWA: Time Weighted Averages

WHMIS: Workplace Hazardous Materials Information System

liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.